



MATTE Clear Coat

2-Component Low Sheen
Protective Clear Coat

- Consistent Sheen
- Waterborne Polyurethane Clearcoat Technology
- Burnish Resistant
- Non-Yellowing
- Silica-Free
- Professional Use

Premium quality 2-part POR-15® Matte Clear Coat seals in any color or patina for a custom low sheen look with amazing results. POR-15® Matte Clear Coat is specifically designed to deliver an extreme level of resistance to scuffing and burnishing, and be a leader in waterborne and even traditional matte clear coatings. POR-15® Matte Clear Coat is formulated with a low VOC, Waterborne Polyurethane Clear Coat Technology that is silica-free. POR-15® Matte Clear Coat has excellent weathering properties and can be used on any substrate that can be cleared with a traditional clear coat.

Note:

STIR ONLY. Always spray a test panel to ensure desired gloss level. Variations in application, temperature, and gun set up can affect the final gloss.



PRODUCT	SIZE	CODE
Matte Clear Coat	1 Gal.	44901
Matte Clear Coat	Quart	44904

Features:

- Can be hand washed with mild detergent and dried with a microfiber cloth
- No flattening agents to add
- Innovative waterborne polyurethane clearcoat technology
- Low VOC
- Industry leading level of resistance to scuffing and burnishing
- Excellent weathering properties
- For use over all basecoats and previously base-coated substrates that are properly prepared
- Seals in color or patina with custom low sheen look



Technical Data

Matte Clear Coat

Two-Component Low Sheen Protective Clear Coat



Dry Time::

Dust Free: 55 minutes
Air Dry (Touch) 2 hours
Baking @ 90°F. 30 minutes

Product mixing

Stir Matte Clear Coat before mixing.
2.4:1 Mixing ratio
2.4 parts Matte Clear
1 Part Hardener
Stir well (do not shake)

Application

CONVENTIONAL - Suggested SPRAY GUN SET UP

1.2 - 1.4 Fluid tip
4 - 8 inch Spray distance
20 - 45 psi Air pressure at regulator
8 - 11 psi at cap
Apply with a 60% overlap 2 full wet coats.

1. Prepare your base as you would most other substrates.
2. Apply 2 full coats or until desired coverage has been achieved.
3. Allow to flash off properly between coats.
4. Allow 15 minutes before baking for 30 minutes @ 90°F.

Safety

MATTE CLEAR COAT PART A

USE WITH ADEQUATE VENTILATION • KEEP OUT OF REACH OF CHILDREN

HEALTH HAZARD INFORMATION: WARNING! Vapor harmful. Causes respiratory, skin and eye irritation. Harmful if swallowed. Do not breathe vapor or spray mist. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and central nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Keep container tightly closed when not in use. Keep away from heat, sparks, open flame or hot surfaces. Avoid contact with eyes, skin and clothing. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.

FIRST AID: IF SWALLOWED: DO NOT induce vomiting; Rinse mouth thoroughly; Seek medical attention if irritation, discomfort or vomiting occurs. FOR SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and shoes and wash clothing before reuse. If symptoms develop seek medical attention. FOR EYE CONTACT: Flush eyes immediately with plenty of fresh water. Remove contact lenses if possible. Continue eye flushing with water for at least 15 minutes. Get medical attention immediately.

FOR INHALATION: If you experience difficulty breathing, leave area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately. If seeking medical attention have label available. For skin protection it is recommended to wear gloves and protective clothing. For eye protection wear safety glasses with side shields or splash-proof goggles.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Transport and Store Upright Only and never in an area of sun or heat exposure. Protect from freezing. Before opening container, read all warning labels. Follow all precautions.

⚠WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.
WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD DUST IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

HAZARDOUS INGREDIENTS: Polyacrylate resin [Proprietary]; Triethanolamine 102-71-6; Propylene Glycol n-Butyl Ether 5131-66-8; 2-(2-(2-butoxyethoxy)ethoxy)ethanol 143-22-6.

Safety

MATTE CLEAR COAT PART B

USE ONLY WITH ADEQUATE VENTILATION • KEEP OUT OF REACH OF CHILDREN

HEALTH HAZARD: WARNING! Vapor harmful. Lung damage and sensitization may be permanent. Causes respiratory, skin and eye irritation. Harmful if swallowed. Do not breathe vapor or spray mist. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and central nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Keep container tightly closed when not in use. Keep away from heat, sparks, open flame or hot surfaces.

Avoid contact with eyes, skin and clothing. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.

FIRST AID: IF SWALLOWED: DO NOT induce vomiting; Rinse mouth thoroughly; Seek medical attention if irritation, discomfort or vomiting occurs. FOR SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and shoes and wash clothing before reuse. If symptoms develop seek medical attention. FOR EYE CONTACT: Flush eyes immediately with plenty of fresh water. Remove contact lenses if possible.

Continue eye flushing with water for at least 15 minutes. Get medical attention immediately. FOR INHALATION: If you experience difficulty breathing, leave area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately. If seeking medical attention have label available. For skin protection it is recommended to wear gloves and protective clothing. For eye protection wear safety glasses with side shields or splash-proof goggles. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Transport and Store Upright Only and never in an area of sun or heat exposure. Protect from freezing. Before opening container, read all warning labels. Follow all precautions.

⚠WARNING: This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

HAZARDOUS INGREDIENTS: Homopolymer of Hexamethylene Diisocyanate 28182-81-2; Hydrophilic Aliphatic Polyisocyanate 666723-27-9; Hexamethylene-1,6-Diisocyanate 822-06-0; Isopropanol 67-63-0.

Refer to Material Safety Data Sheet available upon request for further safety and handling information.

P.O.R. PRODUCTS **800-457-6715**
PORproducts.com

P.O.R. Products, 38 Portman Rd, New Rochelle, NY 10801

© 2018 P.O.R. Products © POR-15 is a registered trademark of P.O.R. Products.