



Rust Remover

Rust Dissolving Solution

- Fast Acting Formula
- Safe to Use On Plastic, PVC, Viton and Most Paints
- Easy to Use
- Reusable and Biodegradable
- No Sanding or Scrubbing
- Water-Based
- Professional Results



POR-15® Rust Remover will safely remove light to even heavy rust completely from metal surfaces and will not affect plastic, PVC, Viton, or most paints. One gallon derusts up to 300 pounds of heavily rusted steel. Rust Remover will not harm unrusted steel and is safe on other metals. Rust Remover has no fumes or bad odors and no VOCs. No sanding or scrubbing required. POR-15® Rust Remover works in as little as 20 minutes for light rust or overnight for heavy rusted metal.

PRODUCT	SIZE	CODE
Rust Remover	1 Gal.	40701
Rust Remover	Quart	40704

Features:

- Environmentally safe
- Water-based
- Safe on delicate metal parts
- No Sanding or scrubbing required
- No VOCs
- Noncorrosive
- Odorless
- Reusable
- Will not harm non-rusted surfaces



Product Information

Rust Remover Rust Dissolving Solution



Product Description

POR-15® Rust Remover will safely remove light to even heavy rust completely from metal surfaces and will not affect plastic, PVC, Viton, and most paints. One gallon derusts up to 300 pounds of heavily rusted steel. Rust Remover will not harm unruled steel and is safe on other metals. Rust Remover has no fumes or bad odors. No sanding or scrubbing required.

Application Information

Directions for use: All of the rusted areas must be submerged in the Rust Remover for it to work. When all of the rust has been removed, rinse the metal pieces with water. POR-15® Remover works in as little as 20 minutes for light rust or overnight for heavy rusted metal.

Safety Information

KEEP OUT OF REACH OF CHILDREN
USE ONLY WITH ADEQUATE VENTILATION

Health Hazard Information: WARNING!: Contains Phosphoric Acid. Skin and eye irritant. Do not ingest. Do not breathe vapor or spray mist. Keep container tightly closed when not in use. Keep away from heat, sparks, open flame or hot surfaces. Avoid contact with eyes, skin and clothing. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.

First Aid: IF SWALLOWED: DO NOT induce vomiting; Rinse mouth thoroughly; Seek medical attention if irritation, discomfort or vomiting. FOR SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and shoes and wash clothing before reuse. If symptoms develop seek medical attention. FOR EYE CONTACT: Flush eyes immediately with plenty of fresh water. Remove contact lenses if possible. Continue eye flushing with water for at least 15 minutes. If symptoms develop seek medical attention. FOR INHALATION: If you experience difficulty breathing, leave area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately. If seeking medical attention have label available.

For skin protection it is recommended to wear gloves and protective clothing. For eye protection wear safety glasses with side shields or splash-proof goggles. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Transport and Store Upright Only and never in an area of sun or heat exposure. Protect from freezing. Before opening container, read all warning labels. Follow all precautions.

CONTAINS: Etidronic acid 28009-21-4; Potassium hydroxide 1310-58-3; Propan-2-ol 67-63-0; Phosphoric acid 7664-38-2.

P.O.R. PRODUCTS 800-457-6715
PORproducts.com

P.O.R. Products, 38 Portman Rd, New Rochelle, NY 10801

© 2018 P.O.R. Products © POR-15 is a registered trademark of P.O.R. Products.