

Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 1 of 11

POR-15 WELD-THRU PRIMER AEROSOL

SECTION 1: Identification

Product identifier

Product name: POR-15 WELD-THRU PRIMER AEROSOL

Product code: 41418

Additional information: No additional information available.



Recommended use of the product and restriction on use:

Relevant identified uses: Paints and coatings.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

P.O.R. Products
38 Portman Road
New Rochelle, NY 10801
914-636-0700

Supplier:

HGLB Holdings
30 Victoria Street
Petone 5012
021 446682
sales@por15nz.com

Emergency telephone number:

ChemTel Inc.

+1 813 248 0585

Poisons Information Center, New Zealand

0800 764 766

SECTION 2: Hazards identification

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2017

HSNO Classification or Subclasses – Physical hazards:

Class	GHS Category	HSNO Category
Flammable aerosols	Category 1	2.1.2A

HSNO Classification or Subclasses – Health hazards:

Class	GHS Category	HSNO Category
Eye irritation	Category 2A	6.4A
Specific target organ toxicity - single exposure	Category 3, central nervous system	6.9B
Specific target organ toxicity - repeated exposure	category 2	6.9B

HSNO Classification or Subclasses – Environmental hazards:

Class	GHS Category	HSNO Category
None known	None known	None known

GHS classification:

Flammable aerosols, category 1

Eye irritation, category 2A

Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 2 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements and Precautionary statements:

H222 Extremely flammable aerosol

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

H373 May cause damage to organs through prolonged or repeated exposure

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P211 Do not spray on an open flame or other ignition source

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P271 Use only outdoors or in a well-ventilated area

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell

P314 Get medical advice/attention if you feel unwell

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents and container as instructed in Section 13

Hazards not otherwise classified:

None known.

SECTION 3: Composition/information on ingredients

Mixture:

Identification	Name	Weight %
CAS number: 67-63-0	Isopropyl Alcohol	7-12
CAS number: 64742-47-8	Mineral Spirits	<2
CAS number: 108-65-6	PM Acetate	<2
CAS number: 13463-67-7	Titanium Dioxide	3-8
CAS number: 67-64-1	Acetone	20-25

Safety Data Sheet
According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 3 of 11

POR-15 WELD-THRU PRIMER AEROSOL

CAS number: 78-93-3	Methyl ethyl ketone	15-20
CAS number: 74-98-6	Propane	12-17
CAS number: 106-97-8	n-Butane	7-12
CAS number: 557-05-1	Zinc stearate	<3
CAS number: 2807-30-9	Glycol Ether EP	<3

Additional information:

None known

SECTION 4: First-aid measures

For advice, contact a Poisons Information Center (e.g. phone Australia 131 126, New Zealand 0800 764 766) or a doctor.

Description of first aid measures

General notes:

Not determined or not available.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position.

Maintain an unobstructed airway.

Get medical advice/attention if you feel unwell.

After skin contact:

Rinse affected area with soap and water.

If symptoms develop or persist, seek medical attention.

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes.

If symptoms develop or persist, seek medical attention.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open.

Remove contact lenses, if present and easy to do so.

Continue rinsing for 15-20 minutes.

Get medical advice if eye irritation persists.

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed:

Acute symptoms and effects:

Not determined or not available.

Delayed symptoms and effects:

Not determined or not available.

Immediate medical attention and special treatment:

Specific treatment:

Safety Data Sheet
According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 4 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Not determined or not available.

Notes for the doctor:

Treat symptomatically.

Workplace Facilities:

Not determined or not available.

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors.

Contents under pressure.

In a fire or if heated, a pressure increase will occur and the container may burst or explode.

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere.

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

Special precautions:

Shut off sources of ignition.

Carbon monoxide and carbon dioxide may form upon combustion.

Heating causes a rise in pressure, risk of bursting and combustion.

Hazchem or Emergency Action Code:

Not determined or not available.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Ensure air handling systems are operational.

Wear protective eye wear, gloves and clothing.

Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

Environmental precautions:

Should not be released into the environment.

Prevent from reaching drains, sewer or waterway.

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing.

Use spark-proof tools and equipment.

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders).

Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 5 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Dispose of contents / container in accordance with local regulations.

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Do not puncture, crush, or incinerate containers, even when empty.

Protect cylinders from physical damage.

Conditions for safe storage, including any incompatibilities:

Protect from freezing and physical damage.

Protect from direct sunlight.

Store in a cool, well-ventilated area.

Store cylinders upright.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

Safe packaging material

Suitable material:

Not determined or not applicable.

Unsuitable material:

Not determined or not applicable.

SECTION 8: Exposure controls and personal protection

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
New Zealand	Isopropyl Alcohol	67-63-0	TWA: 983 mg/m ³ (400 ppm). 15-min STEL 1230 mg/m ³ (500 ppm)
	Methyl Ethyl Ketone	78-93-3	445 mg/m ³ (150 ppm) 15-min STEL 890 mg/m ³ (300ppm)
	Titanium Dioxide	13463-67-7	TWA: 10 mg/m ³
	Acetone	67-64-1	TWA: 1185 mg/m ³ (500ppm); STEL: 2375 mg/m ³ (1000ppm)
	n-Butane	106-97-8	TWA: 1900 mg/m ³ (800ppm)

Biological limit value:

Substance	Identifier	Determinant	Sampling time	Permissible limits
Methyl ethyl ketone	78-93-3	MEK	End of shift.	2 mg/L
Acetone	67-64-1	Acetone	End of Shift	50 mg/L
Isopropyl Alcohol	67-63-0	Acetone	End of shift at end of workweek.	40 mg/L

Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 6 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls

Biological monitoring may also be appropriate for some substances

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Appearance	Aerosol
Odor	Aromatic
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	-44 °C (-47 °F)
Flash point (closed cup)	-19 °C (-2 °F)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Extremely flammable
Upper flammability/explosive limit	12.0 Vol %
Lower flammability/explosive limit	1.7 Vol %
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Between 0.77 and 0.85 (Water equals 1.00)
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Product is not self-igniting
Decomposition temperature	Not determined or not available.

Safety Data Sheet
According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 7 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	In use, may form flammable/explosive vapor-air mixture
Oxidizing properties	Not determined or not available.

Other information

VOC content (less exempt solvents)	59.0%
MIR Value	0.66
Solids Content	15.5%

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity:

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Glycol Ether EP	dermal	LD50 Rabbit male 1,337 mg/kg

Skin corrosion/irritation:

Assessment: Causes skin irritation

Product data: No data available.

Substance data:

Serious eye damage/irritation:

Assessment: Causes serious eye irritation

Product data: No data available.

Substance data:

Name	Result
Acetone	Causes serious eye irritation.
Methyl ethyl ketone	Irritating effect on the eyes.
Isopropyl Alcohol	Causes eye irritation

Safety Data Sheet
According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 8 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Glycol Ether EP	Causes eye irritation.
-----------------	------------------------

Respiratory or skin sensitization:

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Titanium Dioxide	Titanium Dioxide	Airborne, unbound particles of respirable size are known to cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Isopropyl Alcohol	Group 3 - Not classifiable as to its carcinogenicity to humans
Titanium Dioxide	Group 3 - Not classifiable as to its carcinogenicity to humans
Mineral Spirits	Group 3 - Not classifiable as to its carcinogenicity to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: May cause drowsiness or dizziness

Product data: No data available.

Substance data:

Name	Result
Acetone	Specific Target Organ Toxicity, Single Exposure - May cause drowsiness or dizziness.
Methyl ethyl ketone	Component affects the central nervous system.
Isopropyl Alcohol	Component affects the central nervous system.

Specific target organ toxicity (repeated exposure)

Assessment: May cause damage to organs through prolonged or repeated exposure

Product data: No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Safety Data Sheet
According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 9 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Name	Result
Mineral Spirits	May be fatal if swallowed and enters airway.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Hazard to the ozone layer

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

SECTION 14: Transportation information

Road/Rail transport: (NZS 5433:1999)

UN number	1950
UN proper shipping name	Aerosols, flammable


Safety Data Sheet

According to HSNO Regulations


Initial preparation date: 04.06.2018

Page 10 of 11


POR-15 WELD-THRU PRIMER AEROSOL

UN transport hazard class(es)	2.1	
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	

International Air Transport Association Dangerous Goods Regulations (IATA-ICAO)

UN number	1950	
UN proper shipping name	Aerosols, flammable	
UN transport hazard class(es)	2.1	
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	
ERG code	10L	
Excepted quantities	E0	
Passenger and cargo	75 kg	
Cargo aircraft only	150 kg	
Limited quantity	30 kg G	
Additional Information	No additional data	

International Maritime Dangerous Goods (IMDG)

UN number	1950	
UN proper shipping name	Aerosols, flammable	
UN transport hazard class(es)	2.1	
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	
EmS number	F-D, S-U	
Stowage category	For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but "Separated from" class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.	
Excepted quantities	E0	

Safety Data Sheet

According to HSNO Regulations

Initial preparation date: 04.06.2018

Page 11 of 11

POR-15 WELD-THRU PRIMER AEROSOL

Transport in bulk according to Annex II of MARPOL and the IBC CodeL: No data available

SECTION 15: Regulatory information

New Zealand Inventory of Chemicals (NZIoC):

67-63-0	Isopropyl Alcohol	Listed
64742-47-8	Mineral Spirits	Listed
108-65-6	PM Acetate	Listed
13463-67-7	Titanium Dioxide	Listed
67-64-1	Acetone	Listed
78-93-3	Methyl ethyl ketone	Listed
74-98-6	Propane	Listed
106-97-8	n-Butane	Listed
557-05-1	Zinc stearate	Listed
2807-30-9	Glycol Ether EP	Listed

HSNO Classification or Subclasses:

Class	GHS Category	HSNO Category
Flammable aerosols	Category 1	2.1.2A
Eye irritation	Category 2A	6.4A
Specific target organ toxicity - single exposure	Category 3, central nervous system	6.9B
Specific target organ toxicity - repeated exposure	category 2	6.9B

HSNO Group Standard Name :	HSNO Approval Number:
Aerosols (Flammable) Group Standard 2017	HSR002515

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 04.06.2018

Revision Date: New

End of Safety Data Sheet