

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- NSF Approved
- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

8.5W 2FT Plug & Play Glass Tube

LOD-GDMT82F-8.5W40KF

LOD-GDMT82F-8.5W50KF



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-GDMT82F-8.5W40KF	LOD-GDMT82F-8.5W50KF
NSF #	LOD-2FTT8GP-8.5W40K	LOD-2FTT8GP-8.5W50K
Input Wattage (W)	8.5W	
Lumens Delivered (LM)	1,150LM	1,150LM
Efficacy (LM/W)	136LM/W	136LM/W
CRI	80	80
Lifespan	50,000 hours	
Color Temperature	4,000K	5,000K
Wattage Equivalent	15W – 20W	
Dimmable	No	
IP Rating	IP40	
Beam Angle	270	
Input Voltage	AC110-277V	
Power Factor	0.9	
Housing	Glass	
Lens	Frosted	
Mounting	G13	
Size	24"	
THD	10%	10%
Certification	DLC, ETL, NSF	
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
Environment	Indoor	
Warranty	5 years limited	

