

# SAFETY DATA SHEET FLASHPOINT

## **SECTION 1: IDENTIFICATION**

Product Name:

Product Code:

Product Use:

Manufacturer's Name: Address:

Address:

Business Phone:

Emergency Phone: Date of Preparation:

Date of Last Revision: Regulatory Standard: **FLASHPOINT** 

Diesel additive Pittsburgh Power

3600 South Noah Drive Saxonburg PA 16056 USA

724-360-4080

800-633-8253 PERS October 1, 2023

March 1, 2024

CFR29 1910.1200 HazCom

2012

## **SECTION 2: HAZARDS IDENTIFICATION**

GHS-US classification Flammable Liquid 4 Acute toxicity 4 (Oral) Skin Irritation 2 Eye Irritation 2A Carcinogenicity 2 Aspiration Toxicity 1

Hazard pictograms (GHS-US):







Signal word (GHS-US): Danger

Hazard statements (GHS-US): Combustible liquid. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May be fatal if swallowed and enters airways.

Precautionary statements: Keep away from flames/hot surfaces. No smoking. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice or attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/ attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local, regional, national and international regulations.

Other information: None.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Name	CAS Number	%	
Ethylene glycol butyl ether	111-76-2	60 - 80	
2-ethylhexyl nitrate	27247-96-7	10 - 20	
Triethanolamine	102-71-6	1 - 5	
Fatty Acid	Trade Secret	1 - 5	
Benzene, trimethyl-	25551-13-7	1 - 5	
1,3,5-Trimethylbenzene	108-67-8	1 - 5	
Naphthalene	91-20-3	1 - 5	

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

#### **SECTION 4: FIRST AID MEASURES**

First-aid measures after inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact: In case of contact, immediately flush skin with plenty of water. Remove

contaminated clothing and shoes. Wash clothing before reuse. Call a physician if

irritation develops and persists.

First-aid measures after eye contact: In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get

medical attention.

First-aid measures after ingestion: If swallowed, do NOT induce vomiting. Immediately call a POISON CENTER or

doctor/physician. Never give anything by mouth to an unconscious person.

## Most important symptoms and effects, both acute and delayed:

Symptoms/injuries after inhalation: May cause respiratory tract irritation.

Symptoms/injuries after skin contact: Causes skin irritation. Symptoms may include redness, edema, drying, defatting

and cracking of the skin.

Symptoms/injuries after eye contact: Causes serious eye irritation. Symptoms may include discomfort or pain, excess

blinking and tear production, with marked redness and swelling of the

conjunctiva.

Symptoms/injuries after ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting. May be

fatal if swallowed and enters airways. This product may be aspirated into the

lungs and cause chemical pneumonitis.

## Indication of any immediate medical attention and special treatment needed:

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

#### **SECTION 5: FIRE FIGHTING MEASURES**

Suitable extinguishing media: Foam. Dry chemical. Carbon dioxide.

Unsuitable extinguishing media: None known.

Fire hazard: Combustible liquid. Products of combustion may include, and are not limited to:

oxides of carbon.

Protection during firefighting: Keep upwind of fire. Wear full firefighting turn-out gear (full Bunker gear) and

respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to

keep fire-exposed containers cool.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

General measures: Use personal protection recommended in Section 8. Isolate the hazard area and

deny entry to unnecessary and unprotected personnel. Eliminate sources of

ignition.

For containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place

in a suitable container. Do not flush to sewer or allow to enter waterways. Use

appropriate Personal Protective Equipment (PPE).

Methods for cleaning up: Scoop up material and place in a disposal container. Provide ventilation.

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

#### **SECTION 7: HANDLING AND STORAGE**

Additional hazards when processed: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling: Keep away from sources of ignition - No smoking. Use only outdoors or in a well-

ventilated area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use personal protective

equipment as required.

Hygiene measures: Launder contaminated clothing before reuse. Wash hands before eating,

drinking, or smoking.

Technical measures: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions: Keep out of the reach of children. Store in original container protected from direct

sunlight in a dry, cool and well-ventilated area. Keep container tightly closed

when not in use.

Storage temperature: 39 – 120°F

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Ethylene glycol butyl ether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³

OOLIA	COLIX		эо ррш
Triethanolamine (102-71-			
ACGIH	ACGIH	ΓWA (mg/m³)	5 mg/m³
OSHA	Not appl	icable	
Fatty Acid			
ACGIH	Not appl	icable	
OSHA	Not appl	icable	
Benzene, trimethyl- (2555	(1_12_7)		
ACGIH		ΓWA (ppm)	25 ppm
OSHA	Not appl		20 ρρπ
OOTIA	ι τοι αρρι	icabic	
1,3,5-Trimethylbenzene (*	108-67-8)		
ACGIH	Not applicable		
OSHA	Not applicable		
Naphthalene (91-20-3)			
ACGIH	ACGIH	ΓWA (ppm)	10 ppm
OSHA		EL (TWA) (mg/m³)	50 mg/m³
OSHA	OSHA PEL (TWA) (ppm)		10 ppm
0 Ethadla and mitmets (0704	7.00.7\		
2-Ethylhexyl nitrate (2724 ACGIH		icable	
OSHA		Not applicable  Not applicable	
ОЗПА	ινοι αρρι	icable	
Appropriate engineering controls:		Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.	
Hand protection:		Wear chemically resistant pr	otective gloves.
Eye protection:		Wear safety glasses with sid	le shields or goggles.
Skin and body protection:		Wear suitable protective clothing.	
Respiratory protection:	ory protection:  In case of insufficient ventilation, wear suitable respiratory equipment. I selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels, the little selection must be based on known or anticipated exposure levels.		known or anticipated exposure levels, the hazards of

50 ppm

OSHA PEL (TWA) (ppm)

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical state: Appearance: Liquid

No data available

PITTSBURGH POWER

Other information:

Environmental exposure controls:

**OSHA** 

www.Pittsburghpower.com

industrial hygiene and safety practices.

the product and the safe working limits of the selected respirator.

Maintain levels below community environmental protection thresholds.

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established

Color: Light yellow

Odor: Mild

Odor threshold:

pH:

No data available

No data available

Melting point:

Freezing point:

Boiling point:

Flash point:

Relative evaporation rate:

No data available

340°F (171°C)

162°F (72°C)

No data available

Flammability (solid, gas): Flammable

Explosive limits:

Explosive properties:

Oxidizing properties:

Vapor pressure:

No data available

No data available

No data available

No data available

0.6 mm Hg @ 68 °F

Relative density: 0.897

Relative vapor density at 20 °C: 4.1 (Air = 1)Solubility: Water > 90% Partition coefficient: n-octanol/water: No data available Log Kow: No data available Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity: No data available Viscosity, kinematic: No data available Viscosity, dynamic: No data available

## **SECTION 10: STABILITY AND REACTIVITY**

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical Stability: Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

Possibility of hazardous reactions: No dangerous reaction known under conditions of normal use.

Conditions to avoid: Heat. Incompatible materials. Sources of ignition.

Incompatible materials: Oxidizers.

Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Acute toxicity: Harmful if swallowed.

FLASHPOINT	
LD50 oral rat	> 300 but ≤ 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

FLASHPOINT		
LC50 inhalation rat	> 20 mg/l/4h	
Ethylene glycol butyl ether (	l11-76-2)	
LD50 oral rat	1300 mg/kg	
Triethanolamine (102-71-6)		
LD50 oral rat	4190 mg/kg	

LD50 dermal rabbit	> 20 ml/kg	
Fatty Acid		
LD50 oral rat	25 g/kg	
Benzene, trimethyl- (25551-13-7)		
LD50 oral rat	8970 mg/kg	
1,3,5-Trimethylbenzene (108-67-8)		
LC50 inhalation rat	24 g/m³/4h	
Naphthalene (91-20-3)		
LD50 oral rat	490 mg/kg	
LD50 dermal rabbit	> 20 g/kg	
2-Ethylhexyl nitrate (27247-96-7)		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 4820 mg/kg	
LC50 inhalation rat	> 14 mg/l/4h	

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitization: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Suspected of causing cancer.

Ethylene glycol butyl ether (111-76-2)	
IARC group	3 - Not classifiable
Triethanolamine (102-71-6)	
IARC group	3 - Not classifiable
Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
<b>3,</b> 3, ,	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation: May cause respiratory tract irritation.

Symptoms/injuries after skin contact: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting. May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis.

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecology - general: May cause long-term adverse effects in the aquatic environment.

Persistence and degradability

#### **FLASHPOINT**

Persistence and degradability Not established.

Bioaccumulative potential

#### FLASHPOINT

Bioaccumulative potential Not established.

Mobility in soil: No additional information available

Other adverse effects: Effect on the global warming - No known ecological damage caused by this product.

#### SECTION 13: DISPOSAL CONSIDERATIONS

Waste disposal recommendations: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information: Handle empty containers with care because residual vapors are flammable.

#### SECTION 14: TRANSPORT INFORMATION

UN number: NA1993

Proper shipping name: Combustible liquid, n.o.s., (Ethylene glycol monobutyl ether)

Transport hazard class(es): Combustible liquid

Packing group: III

This product may be reclassed as a combustible liquid. Refer to 49 CFR Section 173.150.

This product is not regulated for road or rail transportation in the United States if packaged in non-bulk containers equal to or less than 119 Gallons/450 liters.

#### SECTION 15: REGULATORY INFORMATION

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Federal regulations:

1,3,5-Trimethylbenzene (108-67-8)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Naphthalene (91-20-3)	
Subject to reporting requirements of United States SARA Section 313	

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %

## State regulations:

FLASHPOINT	
State or local regulations	This product contains a chemical known to the State of California to
	cause cancer.

# **SECTION 16: OTHER INFORMATION**

Other information: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.