

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date 02/07/17:

Supersedes:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Max Mileage Fuel Catalyst
Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Aromatic Solvent (Blend of Aromatic Hydrocarbons)

1.3. Details of the supplier of the safety data sheet

Better Diesel FBC, Inc.

1.4. Emergency telephone number

Emergency number : 1-703-527-3887 (CHEMTREC)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

| | |
|-------------------|------|
| Flam. Liq. 4 | H227 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2A | H319 |
| Carc. 2 | H351 |
| Repr. 2 | H361 |
| Aquatic Acute 2 | H401 |
| Aquatic Chronic 2 | H411 |

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H227 - Combustible liquid
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer
H361 - Suspected of damaging fertility or the unborn child
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, open flames, sparks. - No smoking
P264 - Wash hands, forearms and face thoroughly after handling
P273 - Avoid release to the environment
P280 - Wear eye protection, protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of soap and water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see first aid instructions on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder to extinguish
P391 - Collect spillage
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % |
|---|----------------------|-----------|
| Benzene, ethylenated, residues, distillation lights | (CAS No) 178535-25-6 | 60 – 100* |
| Proprietary Additives | | 0-5* |
| Proprietary Additives | | 0-3* |
| Other Aromatics | | 0 – 2* |
| | | |
| | | |

*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person. |
| First-aid measures after inhalation | : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen. |
| First-aid measures after skin contact | : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention. |
| First-aid measures after eye contact | : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing. |
| First-aid measures after ingestion | : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|--------------------------------------|--|
| Symptoms/injuries | : Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. |
| Symptoms/injuries after inhalation | : May cause respiratory irritation. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |
| Symptoms/injuries after eye contact | : Causes serious eye irritation. |
| Symptoms/injuries after ingestion | : May cause gastrointestinal irritation. |
| Chronic symptoms | : Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. |

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry chemical.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
Explosion hazard : Product is not explosive.
Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Precautionary measures fire : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Scoop solid spill into closing containers or bags. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Avoid breathing mist, vapours. Keep away from sources of ignition - No smoking. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Keep the container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Benzene, ethylenated, residues, distillation lights (178535-25-6) | |
|--|--|
| Remark (ACGIH) | OELs not established |
| Remark (OSHA) | OELs not established |
| Naphthalene (91-20-3) | |
| ACGIH TWA (ppm) | 10 |
| ACGIH STEL (ppm) | 15 |
| Remark (ACGIH) | 5 TWA notice of intended changes TLVs |
| OSHA PEL (TWA) (mg/m ³) | 50 |
| OSHA PEL (TWA) (ppm) | 10 |
| Benzene, triethyl- (25340-18-5) | |
| Remark (ACGIH) | OELs not established |
| Remark (OSHA) | OELs not established |
| Ethylbenzene (100-41-4) | |
| ACGIH TWA (ppm) | 20 |
| Remark (ACGIH) | upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment |
| OSHA PEL (TWA) (mg/m ³) | 435 |
| OSHA PEL (TWA) (ppm) | 100 |
| OSHA PEL (STEL) (mg/m ³) | 545 |
| OSHA PEL (STEL) (ppm) | 125 |
| Toluene (108-88-3) | |
| ACGIH TWA (ppm) | 20 |

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-------------------------------------|------------------------------|
| Toluene (108-88-3) | |
| Remark (ACGIH) | Visual impair; female repro; |
| Cumene (98-82-8) | |
| ACGIH TWA (ppm) | 50 |
| OSHA PEL (TWA) (mg/m ³) | 245 |
| OSHA PEL (TWA) (ppm) | 50 |

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective goggles. Protective clothing.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

: Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : Liquid |
| Appearance | : Clear Non-viscous liquid. |
| Color | : Deep Orange to Amber. |
| Odor | : Aromatic. |
| Odor Threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : < -50 °C (- 58 °F) |
| Freezing point | : No data available |
| Boiling point | : 180 - 277 °C (356 - 531 °F) |
| Flash point | : 71 - 88 °C (160 - 190 °F) (PMCC) |
| Auto-ignition temperature | : 400 °C (752 °F) estimated |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : 0.05 mm Hg (0.001 psi) @ 38 °C (100 °F) |
| Relative vapour density at 20 °C | : 5.5 (Air = 1) |
| Relative density | : 0.91 (Water = 1) |
| Solubility | : Water: ≈ 20 ppm @ 20 °C (68 °F) |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

No additional information available

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Strong oxidizing materials may ignite this material.

10.4. Conditions to avoid

Avoid contact with : Incompatible materials.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Carbon monoxide. Asphyxiants.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Naphthalene (91-20-3) | |
|--------------------------------|-----------------------------|
| LD50 oral rat | 1110 mg/kg |
| LC50 inhalation rat (mg/l) | > 340 mg/m ³ 1 h |
| Ethylbenzene (100-41-4) | |
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | 15400 mg/kg |
| LC50 inhalation rat (mg/l) | 17.2 mg/l/4h |
| Toluene (108-88-3) | |
| LD50 oral rat | 2600 mg/kg |
| LD50 dermal rabbit | 12000 mg/kg |
| LC50 inhalation rat (mg/l) | 12.5 mg/l/4h |
| Cumene (98-82-8) | |
| LD50 dermal rabbit | 12300 µl/kg |
| LC50 inhalation rat (ppm) | > 3577 ppm 6 h |

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

| Naphthalene (91-20-3) | |
|--|---|
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 3 - Reasonably anticipated to be Human Carcinogen |
| Ethylbenzene (100-41-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| Cumene (98-82-8) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| Benzene (71-43-2) | |
| IARC group | 1 - Carcinogenic to humans |
| National Toxicology Program (NTP) Status | 2 - Known Human Carcinogens |

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified
Symptoms/injuries after inhalation : May cause respiratory irritation.
Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye irritation.

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion : May cause gastrointestinal irritation.
Chronic symptoms : Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

AS-220

| | |
|-------------------------------|---------------------------|
| Persistence and degradability | No information available. |
|-------------------------------|---------------------------|

12.3. Bioaccumulative potential

AS-220

| | |
|---------------------------|---------------------------|
| Bioaccumulative potential | No information available. |
|---------------------------|---------------------------|

12.4. Mobility in soil

AS-220

| | |
|----------------|---------------------------|
| Ecology - soil | No information available. |
|----------------|---------------------------|

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : NA1993 Combustible liquid, n.o.s. (Contains: Polyethylbenzene, Triethylbenzene, Naphthalene), 3, III

DOT NA no. : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.
Contains: Polyethylbenzene, Triethylbenzene, Naphthalene)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

Additional information

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transport by sea

Transport document description : UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Contains: Polyethylbenzene, Triethylbenzene, Naphthalene), 9, III, MP

UN-No. (IMDG) : 3082

Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains: Polyethylbenzene, Triethylbenzene, Naphthalene)

Class (IMDG) : 9 - Miscellaneous dangerous substances and articles

Hazard labels (IMDG)





Packing group (IMDG) : III - substances presenting low danger

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

| | |
|--------------------------------|---|
| Transport document description | : UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Contains: Polyethylbenzene, Triethylbenzene, Naphthalene), 9, III, MP |
| UN-No.(IATA) | : 3082 |
| Proper Shipping Name (IATA) | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains: Polyethylbenzene, Triethylbenzene, Naphthalene) |
| Class (IATA) | : 9 - Miscellaneous Dangerous Goods |
| Hazard labels (IATA) |   |
| Packing group (IATA) | : III - Minor Danger |
| Other information | : Per IATA special provision A197, UN3082 substances may be shipped as "not restricted" provided that the net quantity in any receptacle does not exceed 5 kg or 5L and the packaging used meets defined standards. |

SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|---|---|
| AS-220 | |
| All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory or are exempt | |
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard |
| Naphthalene (91-20-3) | |
| Section 302 (EHS) TPQ | |
| Section 304 EHS RQ | |
| CERCLA RQ | 100 lb |
| Section 313 | Listed on US SARA Section 313 |
| Ethylbenzene (100-41-4) | |
| Section 302 (EHS) TPQ | |
| Section 304 EHS RQ | |
| CERCLA RQ | 1000 lb |
| Section 313 | Listed on US SARA Section 313 |
| Toluene (108-88-3) | |
| Section 302 (EHS) TPQ | |
| Section 304 EHS RQ | |
| CERCLA RQ | 1000 lb |
| Section 313 | Listed on US SARA Section 313 |
| Cumene (98-82-8) | |
| Section 302 (EHS) TPQ | |
| Section 304 EHS RQ | |
| CERCLA RQ | 5000 lb |
| Section 313 | Listed on US SARA Section 313 |
| Benzene (71-43-2) | |
| Section 302 (EHS) TPQ | |
| Section 304 EHS RQ | |
| CERCLA RQ | 10 lb |
| Section 313 | Listed on US SARA Section 313 |

15.2. International regulations

No additional information available.

15.3. US State regulations

California Proposition 65

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

| | | | | |
|--|---|---|---|--|
| Naphthalene (91-20-3) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | 5.5 µg/day |
| Ethylbenzene (100-41-4) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | 54 (inhalation) µg/day 41 (oral) µg/day |
| Toluene (108-88-3) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Maximum Allowable Dose Levels (MADL) |
| No | Yes | No | No | 7000 µg/day |
| Cumene (98-82-8) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | Not available |
| Benzene (71-43-2) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | Yes | No | Yes | 6.4 (oral) µg/day 13(inhalation) µg/day |
| Naphthalene (91-20-3) | | | | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List | | | | |
| Ethylbenzene (100-41-4) | | | | |
| U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List | | | | |
| Toluene (108-88-3) | | | | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List | | | | |
| Cumene (98-82-8) | | | | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List | | | | |
| Benzene (71-43-2) | | | | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List | | | | |
| SECTION 16: Other information | | | | |

Indication of changes : Revision 6.0
 Revision date : 02/07/2017
 Other information : Author: BCS.

Max Mileage Fuel Catalyst

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

| | | |
|---------------------|---|----|
| Health | : | 3* |
| Flammability | : | 2 |
| Physical | : | 0 |
| Personal Protection | : | |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product