

Overhead Holders & Stops



Innovation, Quality,
Customer Service...

4000 Series Concealed Mount, Medium Duty



Standard Features

- Concealed mount
- Medium duty
- Stop, hold-open and friction functions available
- Single or double acting doors
- Non-handed
- For interior use on moderate traffic and medium weight doors
- Standard installation from 85° to 110° of opening (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- 1-3/8" minimum door thickness
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 2 lbs.

Options Available

(see page B-5 for details)

- **SEC** - Security fasteners
- **LL** - For lead-lined door applications
- **N** - All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- **T** - Threaded pivot screw and nylon washer to replace jamb bracket
- **HC** - Hold Closed
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom application and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

Material

- **Stainless steel** is the standard base material for arm, channel and jamb bracket for all finishes.

Door Frame Opening		Model Number		
Hinges, Swing Clear or Offset Pivots	Center Hung	Hold Open	Stop	Friction
18" - 23-15/16" *	-	4011	4021	4031
24" - 29-15/16"	-	4012	4022	4032
30" - 35-15/16"	32" - 37-15/16"	4013	4023	4033
36" - 48"	38" - 48"	4014	4024	4034
ANSI Code		C04511	C04541	C04531

* Butt Hinges only for this size

Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable



Architectural Builders Hardware Manufacturing, Inc.
1222 Ardmore Avenue, Itasca, IL 60143
Tel: 630-875-9900 • Fax: 630-875-9918 / 800-932-9224
Web: www.abhmfg.com • Email: abhinfo@abhmfg.com