



## 293D

Constant Latching Flush Bolt Set for Inactive Metal Doors

### Applications



### PRODUCT SPECIFICATIONS

**Bolt:**

Backset: 3/4" (19 mm)

**Bolt Throw:**

3/4" (19 mm)

**Box Quantity:**

1

**Case Quantity:**

10

**Category:**

Flush Bolts & Coordinating Devices

**Certifications:**

3 hour fire rating on metal doors up to 4' wide x 9' tall (A, B, C, D, and E label rating)  
ANSI A156.3 Type #27

**Faceplate:**

1" x 6-3/4" (25 mm x 172 mm)

**Fasteners:**

Eight #8 x 1" combination screws

**Finishes:**

US10B, US32D

**Flattened Round Bolt Head:**

Square bolt head 1/2" (13 mm)

**Material:**

Stainless steel and brass with steel components

**Notes:**

Thermal lock automatically locks inactive door under high fire/heat conditions  
280X dust proof strike are recommended for use with these sets  
3-hour fire rating for metal doors up to 4 feet wide x 9 feet tall  
Consists of one 292S and one 293S for two point latching  
Inactive door remains latched until active door is opened, releasing the automatic bottom bolt  
Top bolt can be manually released by pressing plunger  
Inactive door will re-latch automatically when closed  
Non-handed  
Bolt head rods are adjustable  
To only be used with non-beveled doors

**T-Strike:**

1-1/8" x 2-3/4" (28 mm x 70 mm)