

Z8536NHR / Z8564NHR

36/64-Channel 4K H.265+ Network Video Recorder



- H.265+/H.265/H.264 decoding
- Support 36- or 64-channel 4K IP cameras input
- Support 16 channels real-time playback synchronously
- HDMI output up to 4K high definition
- Intelligent video analytics functions (up to IPC)
- DHCP, DNS, DDNS, NTP, UPNP, RTSP, etc.
- Support multiple web browsers login
- P2P cloud service supported
- ONVIF Profile S compatible

System Overview

NVR of the Z8000NHR series could deliver up to 4K resolution excellent image over advanced H.265+ decoding. It's an ideal consideration for the balance of quality, performance, and budget.

The user-friendly GUI provides intuitive shortcut operations, remote control, management, flexible storage, and playback. Powered by the reliable interoperability and ONVIF Profile S, it's compatible with plenty of 3rd-party IPC or crossing platform VMS. The devices can be used in governmental institutions, bank sectors, manufacturers, educational or commercial projects.

Functions

IVA functions supported (Intelligent Video Analytics) such as Line Crossing / Target Counting / Object Left/Lost / Intrusion / Scene Change / VQD, etc. (up to IPC)

User-friendly & full function VMS / Mobile App

Alarm events linkage actions such as email, audio, buzzer and alarm push message to Mobile App and VMS

Technical Parameters

Model	Z8536NHR	Z8564NHR	
System			
Main Processor	Multi-core embedded processor		
Operating System	Embedded LINUX		

Z8536NHR / Z8564NHR

Video and Audio			
Max IPC Input	36CH	64CH	
Two-way Talk	Support		
Audio Compression	G.711u		
Live View			
Display Split	1/4/6/9/16/36 CH	1/4/6/9/16/36/64 CH	
Resolution	8MP(3840*2160) / 5MP(2592*1944) / 2MP(1920*1080)) / 1.3MP(1280*1024) / 1Mp(1280*720) / D1(1024*768)	
Live View Capability	36CH@D1(25/30fps)		
Recording			
Video Compression	H.265+/H	H.265+ / H.265 / H.264	
Recording Resolution	8Mp/5MP/4MP/3MP/1080P/960P/720P/D1		
Max. Decoding Capability	36CH@D1(25/30fps)		
Incoming Bandwidth	216 Mbps	512 Mbps	
	Main Stream: 256Kbps ~ 8192Kbps Sub Stream: 50Kbps ~ 700Kbps		
Bit Rate			
Record Mode	Schedule, Manual, Motion Detection, IVA Events Alarm		
Record Interval	1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec		
Playback and Backup			
Playback Channel	16CH		
Search Mode	Time/ Date, Alarm Types, IVA Search		
Playback Function	Play, Stop, Play Forward, Play Backward, 30 Seconds Forward, 30 Seconds Backward, Fast Play, Slow Play, Single Frame Play, Hide/Show Time Bar, Backup, Snapshot, Full Screen		
Backup Mode	USB Device / Network Remote		
IVA Alarm			
Local IVA Functions	Line Crossing / Target Counting / Object Left/Lost / Intrusion / Scene Change / VQD		
Regular Detection	Motion Detection / Video Shelter / Video Loss		
Al Search	Support search target video by multiple intelligent conditions		
Network			
Network Protocol	TCP/IP, HTTP, DDNS, SMTP(SSL), DHCP, PPPoE, UPnP, NTP, P2P		
Max. Online User	5		
Web Browser	Internet Explorer		
Operation System	Windows		
Management Platform	AntarVis 2.0		
Mobile Application	AntarView Pro (iOS & Android)		
P2P Cloud Service	Support		
Interoperability	ONVIF Profile S, SDK, CGI, API		

Z8536NHR / Z8564NHR

Storage & Auxiliary Interface				
SATA Ports	9 SATA Ports, up to 8 TB capacity			
eSATA	Support			
Raid 0/1/5/6/10	Support			
HDMI	1*HDMI (4K)			
VGA	1920*1080/60Hz, 1280*1024/60Hz			
Network Interface	2 RJ-45 Port (1000Mbps)			
PoE Ports	N/A			
USB	1*USB 2.0, 1*USB 3.0			
Audio Input/Output	1/1			
Alarm Input/Output	4/4			
RS-485	Support			
Power				
Power Supply	AC100~240V, 47Hz~63Hz			
Power Consumption	35W (Without HDD)			
General				
Casing	20			
Working Temperature	-10°C ~ 55°C / 14°F ~ 131°F			
Working Humidity	10% ~ 90%			
Dimensions (L*W*H)	412 * 430 * 87 (mm)			
Net Weight	7kg (without HDD)			
Gross Weight	7.5kg (without HDD)			


Order Information

Name	Model	Description
NVR	Z8536NHR	36CH H.265+ NVR, 9SATA
	Z8564NHR	64CH H.265+ NVR, 9SATA

Dimensions (mm)

Rear Panel







1600 Union Hill Rd, Alpharetta, GA 30005 Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zktecousa.com • www.zktecousa.com

- © Copyright 2020. ZKTeco Inc. ZKTeco Logo and ZKTeco USA Logo have registered trademarks of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.