

FEATURES

- 4pcs 2MP In/Outdoor Turret Camera
- Includes 8-Channel HD DVR
- Audio Recording with Built-in Mic
- Bolide QuickConnect Mobile App
- Bolide VMS Software for PC and Mac
- Power Supplies Included



CAMERA SPECIFICATIONS

Image Sensor	1/3" Progressive CMOS
Min. Illumination	0.05 lux @ F1.2(AGC ON) B/W 0 lux @ IR ON
Video Output	BNC
Resolution	2MP 1920 (H) × 1080 (V)
Max Framerate	AHD/TVI/CVI: P/@25fps N/ @ 30fps CVBS: 960H
Focal Length	2.8mm Fixed Lens
Max. Aperture Ratio	F2.0
Field of View	H: 88.24° / V: 48.71° / D: 104.37°
Min. Object Distance	2.62 FT
Audio	Yes, Built-in Mic (TVI Mode Only)
IR Distance	65 FT
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Comp.	Off / User BLC
WDR	D-WDR (Off/On)
D. Noise Reduction	2D DNR
White Balance	ATW
Remote Interface	ACP (AHD Coax Protocol)
Operating Temp.	-22°F ~ 122°F / 90%
Weather Rating	IP66
Input Voltage	12VDC
Power Consumption	IR OFF ≤0.5W , IR ON ≤3.5W
Weight	0.7 lb
Dimensions	3.93 in x 3.54 in

CAMERA IMAGE



CAMERA KIT PACKAGING



DVR SPECIFICATIONS

Recording Bandwidth

Inputs	8Mbps ~ 40Mbps IP Bandwidth Max is 8Mbps, Decrease One Analog Channel Can Increase 4Mbps (Default Decoding Performance 1080P 60FPS)
Output	56Mbps
Analog Video Input	8 Channels BNC

Live

IP Video Input	2 Channels
Composite Video In	Up to 10 Channels (Analog+ IP)

Recording and Playback

Compression	Audio: G.711a Video : H.264/H.265
Display Resolution	1080N/720P/960H:30fps IP:1080P/720P Single IP Channel Preview up to 2MP 30FPS Multi-Channel, Preview Only Sub-Stream
Speed	<u>Main Stream:</u> 1080N (960*1080):30FP 720P: 30FPS / Channel IP: PAL:25FPS / Channel NTSC: 30FPS / Channel <u>Sub-Stream:</u> PAL : 704*576: 10FPS / Channel NTSC : 704*480: 10FPS / Channel
Playback	60FPS (Max 4CH Playback)
Playback Function	Fast Forward / Backward (2x, 4x, 8x,16x) Slow Forward (1/2x, 1/4x, 1/8x,1/16x)
Audio	Yes, Audio Over Coax
Audio In/Out	No
Video Output	1x HDMI
Ethernet	1x RJ45 10/100Base-T
USB	2x USB 2.0
HDD	1x SATA Up to 12TB

General

Dimensions	9.05in (L) x 8.46in (W) x 1.85in (H)
Voltage / Current	12VDC 2A
Power Consumption (Excluding HDD)	4W
Operating Temp.	32°F ~ 104°F
Op. Humidity	Less than 90%RH

Remote Access

Bolide QuickConnect App For iOS and Android

Bolide VMS For PC and Mac (Free Download)

DVR IMAGE

