

FEATURES

- 12x Optical Motorized Zoom Lens
- H.265 Compression
- 3.6" Explosion-Proof Housing with
- Quick-Install Design
- 90° Vertical, 355° Horizontal Pan / Tilt
- Built-in IR-Cut
- IR Up to 164 Feet
- 48 Pre-set Positions and One Watch Point

SPECIFICATIONS

Image Sensor	1 / 2.7" CMOS
Resolution	5MP 2592 (H) x 1944 (W)
Min. Illumination	Color 0.05lux @ F1.2 (AGC ON)
Signal-to-Noise Ratio	50dB
Power Zoom (mm)	5-60mm
Vertical Rotation	90°
Horizontal Rotation	355°
Infrared Light	Double Array Lamp
Infrared Distance	Up to 164 Feet
Day/Night Mode	Auto / Day / Night
Backlight Mode	Close / Open
Color Density	Adjustable via Menu
Contrast	Adjustable via Menu
Digital Noise Reduction	3D Digital Noise Reduction
White Balance	Manual / Automatic White Balance
Electronic Shutter	Auto, 1/25s – 1/10,000s
Preset Positions	48
Watch Point	1
App Control	Supports Mobile App Control
Ethernet	RJ-45 (10/100BASE-T)
Video Compression	H.265 / MJPEG
Video Transmission Rate	Variable / Constant (128Kbps~12Mbps Second)
Resolution	5MP @ 20FPS
Bit Stream	Double Stream
Protocol	ONVIF 2.4
Operating Temp. and Humidity	-40°F ~ 131°F < 90% RH
Storage Temp. and Humidity	-22°F ~ 140°F < 90% RH
Weather Rating	IP66
Input Voltage	12VDC±10%
Power Consumption	800mA / 3.1W (Peak 1A/8W)



PHYSICAL CHARACTERISTICS

Color / Material	White / Metal
Lens Cover	High Intensity Gray - Black High Transparency Plexiglass
Connection Port	RJ-45 Port / 12VDC Plug
Dimension	4.73 in (W) x 4.49 in (H)
Weight	1.41 lbs

DIMENSIONS

