

PRODUCT FEATURES

- » The alarm kit includes a central gateway, 4 contact sensors, a PIR sensor, a remote key, a temperature and humidity sensor (repeater), and a smart plug.
- » Link your home alarm, video and automation in one app.
- » Get alerts when your home environment changes, doors or windows open, or motion is detected.
- » Arm and disarm the whole home alarm system with one push of a button on the remote key, or with one click from the app.
- » With the SOS button on the remote key you can receive alerts on your mobile device.
- » With the smart plug you can switch home automation on/off with the mobile app. For example, turn on the air conditioner or make a cup of coffee for when you arrive home in few minutes.
- » With the additional cameras in the series (door bell camera, Wi-Fi camera, floodlight camera), you can receive alarm alerts in the same app (cameras are not included in this kit)



DEVICE CENTER

- Max. 128 zigbee equipment can be connected, including alarm sensors, switches, plugs, controllers etc.
- Unique device identification and automatically connect to the network, code pairing not need
- Communication distance: 50M
- Power: DC 5V 300mA
- Working Frequency: 2405M~2480MHZ

ENVIRONMENTAL SENSOR

- Can display your home's brightness, temperature, humidity in the app's homepage
- Can set device linkage according to environment parameters. For example, turn on the air conditioner when the temperature reaches a predetermined degree
- Power input USB DC5V1A
- Installation: ceiling or wall mount
- Communication distance: 50M



SMART PLUG

- Input Voltage AC 175V~235V and consumption 16A (2000W)
- Material: Flame retardant ABS
- Communication: ZigBee Protocol
- Support multi group On/Off timing switch
- Static power consumption: <0.1W
- Wireless output: -10 dBm --5dBm
- Support US, UK, Europe, Australia etc. plug
- Supports programming so that user can define fast key to open or close certain plugs automatically



SMART PIR SENSOR

- With 2 settings, alarm and trigger linkage
- Low power consumption design
- Auto threshold value adjusting technology, avoiding mis-alarm effectively.
- Auto temperature compensation, avoiding low sensitivity due to temperature changes
- Low battery alert
- Working voltage: 3.0V
- Can add to routine or linked to other device
- ZigBee Protocol





CONTACT SENSORS (4 ITEMS)

- With low power consumption ZigBee module
- Can identify NO or NC status
- Low battery alert
- Working voltage: 3.0V
- Can add to routine or linked to other device
- Sensitivity 15mm
- Ideal for door and window monitoring



REMOTE CONTROL

- Arm or disarm the entire home security system with one key
- With the SOS button you will receive alerts immediately to your mobile
- Enable all exterior sensors and deactivate the internal sensors so that you can move safely in your home

INSTALLATION OF EQUIPMENT

