DVAXD2504

4CH 5M-N 5-in-1 XVR



Key features

- TVI / AHD / DVR / NVR / CVI 5-in-1 function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.
- Supports various mobile phone monitoring (iPhone Android).
- Support multiple web browsers (IE / Chrome / Firefox / Safari).
- · Support VGA, HDMI output at the same time.
- Support STVI function.
- · Support coaxial audio
- support multi-languauge





Index	Description	Index	Description
1	Video In	6	RJ45
2	Video Out	7	USB
3	HDMI	8	Power
4	Audio In	9	VGA
(5)	Audio Out		

Specifications				
System				
Compression	H.265			
O/S	Embedded Linux O/S			
Video and Audio				
Video Input	4CH,BNC			
	4*5MN@20fps (4 in 1)			
Preview Ability	4*4MN@25fps (4 in 1)			
	4*1080N@25fps (4 in 1)			
	4*5MN@12fps (4 in 1)			
Coding Ability	4*4MN@17fps (4 in 1)			
	4*1080N@15fps(4 in 1) 4*5MN@12fps(4 in 1)			
Decoding Ability	4*4MN@17fps (4 in 1)			
,	4*1080N@15fps (4 in 1)			
Video Output	1CH VGA;1CH HDMI			
Channel Mode	Support any channel mode combination (5MN analog +			
	1080P digital)			
Audio In & Out	1/1, RCA			
Video Standard PAL/NTSC				
Storage SATA	1x SATA Interface			
Capacity	Up to 8TB Max.			
File Format	H.264 \ H.265 \ AVI			
- 110 1 01111010	USB			
Playback and Backup Video Playback Auto/Timing/ Motion detection				
Sync Playback	4CH			
	Point-in-time search, calendar search, event search,			
Search Mode	channel search			
Network				
Ethernet	10 / 100 Mbps,1 RJ45			
Network Function	TCP/IP, DHCP, DDNS, NTP, SMTP			
Interoperability	ONVIF Standard			
Smart Phone	iPhone, Android			
Hardware				
Network Interface	1x RJ45			
USB Interface	2x USB2.0			
PTZ Interface	Support RS485 PTZ			
Controlling Device	Mouse Not Support			
Alarm Input Alarm Output	Not Support Not Support			
Special	ινοι συρμοτι			
Multi-Screen Display	1/4			
Alarm Method	Email Alarm			
Digital Zoom	Not Support			
Two-Way Talk	Support			
Alarm Snapshot	Support			
Intelligent Analysis	Support Motion Detection、Video Tampering、Video loss			
General				
Power Supply	DC12V /2A			
Consumption	≤ 8 W (with out HDD)			
Working Temperature	-10° C ~60° C			
Working Humidity	10% ~ 90% Humidity			
Dimensions	250x223x42mm			
Weight	800g			