

FEATURES

- Plug and Play (with Bolide iPac NX NVRs)
- Up to 8 Views on One Camera
- VR Mode, Cylinder View
- 180° Panoramic and Double Panoramic Views
- Built-in Microphone
- Built-in POE

SPECIFICATIONS

Image Sensor	1/1.7" Progressive CMOS
Resolution	9MP 3000(H)×3000(V)
Min. Illumination	Color 0.01lux @ F1.2 (AGC ON); B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Lens	2.0mm, Angle of view: 360°
F No.	F 2.4 ±5%
Day & Night	IR Cut Filter with Auto Switch
WDR	Digital
Video Compression	H.265 / H.264
Video Bit Rate	8Kbps ~ 8Mbps
Triple Stream	Yes
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness Adjustable
BLC	Support
ROI	Support
Privacy Mask	Support
Video Analytics	NA
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Compatibility	ONVIF Version 2.6
Interface	RJ45 10M/100M Ethernet Interface x1
LED	3pcs(SMD)
IR Range	Up to 5m
Alarm Trigger	Yes
Audio	Yes
Built-in Microphone	Yes
Reset Button	Yes
POE	Yes
Weather Rating	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 7W
Dimension	Ø120*55mm
Weight	~400g



CHARACTERISTICS

Frame Rate	Main Stream 9MP (3000x3000), 2560x2560, 2160x2160, 1520x1520, 1080x1080, 720x720
	Substream 2MP (1080x1080), 720x720, 480x180, 240x240
	Mobile Stream 480x480, 240x240
Storage Temperature	-30° ~ 60°C
Operating Temperature	-30° ~ 55°C