


# EAX® EXIT ALARMS

## EAX-300

### Battery Powered Door Propped Alarm

The Detex EAX-300 Series is designed for applications where doors may be used for egress or ingress, but may not be held or propped open. Door open times from 1 second to 4 minutes (15 second default) are field selectable. The smaller size makes installation quick and easy.

Shown with mortise cylinder  
(cylinder sold separately)



#### Benefits

- Low cost, solution to propped open doors
- Door or wall mount
- Helps keep energy costs down by ensuring doors are closed
- Quick, easy installation saves time and money
- Alarm silences when door is closed, no waiting for key-holder to arrive

#### Features

- Secure, tamper resistant housing
- Patented plastic template assures accurate installation by providing foolproof alignment with internal magnetic door contact
- Tapered cover allows for installation on narrow stile doors
- Intelligent circuit senses the external magnet location automatically and sets the correct door handing
- 100 dB piezo alarm
- 9VDC battery operated with Low Battery Alert
- LED visual arming indicators

#### Field Selectable Door Prop Times

Door Prop Timer	LED indication
1 second	1 GREEN flash
15 seconds (Default)	1 RED flash - 5 GREEN flashes
30 seconds	3 RED flashes
45 seconds	4 RED flashes - 5 GREEN flashes
1 minute	1 RED & GREEN simultaneous flash
2 minutes	2 RED & GREEN simultaneous flashes
4 minutes	4 RED & GREEN simultaneous flashes

## Mechanical Options

- EAX-300 may be ordered in several kit configurations:

SK1 Kit allows for wall mounting and includes (1) white MS-1039S door contact

SK2 Kit allows for wall mounting and includes (2) white MS-1039S door contacts

SK3 Kit allows for wall mounting and includes (1) brown MS-1059S door contact

SK4 Kit allows for wall mounting and includes (2) brown MS-1059S door contacts

SK5 Kit allows for wall mounting and includes (1) grey MS-2049S door contact

SK6 Kit allows for wall mounting and includes (2) grey MS-2049S door contacts

- KS - Key Stop, factory installed
- SI - Status Indicator On

## Electrical Options

- Weatherized for use on gates or doors that are subjected to inclement weather

## Accessories

- MC65 - Detex Mortise Cylinder pre-installed at factory

- IC7 - 7 pin interchangeable core housing, pre-installed at factory (Compatible with most standard 7 pin IC format cores)

- IK7 - Cylinder InstaKey Housing

## Technical Information

- Machine and self-drilling screws

- Optional Cylinder Nut Wrench P/N: 103779





## Finishes

- GY - Grey


- BK - Black

## Dimensions

Front and Side View



## Riser Diagram



## Listings and Approvals



UL Listed Miscellaneous Fire Door Accessory



ANSI/BHMA A156.29

## Detex Limited Warranty

3 Year Limited Manufacturer's Warranty



Detex Corporation  
302 Detex Drive  
New Braunfels, Texas 78130-3045 USA  
PH. (830) 629-2900  
(800) 729-3839  
FAX (800) 653-3839  
<http://www.detex.com>  
USA Sales:  
[marketing@detex.com](mailto:marketing@detex.com)  
International Sales:  
[export@detex.com](mailto:export@detex.com)

Cancer & Reproductive Harm - [www.detex.com/prop65](http://www.detex.com/prop65)