

CONNECT WITH US



DATA SHEET 2019

KL2O



A simple robust mechanical lock. Tough alloy front and handle. Flush mounted ideal for personal storage in offices, schools and colleges. The user selects their own 4 digit code and this remains unchanged until they wish to alter it. The user can change their code at anytime and the KL20 has the added security and convenience of auto scramble. The dials automatically scramble to 0-0-0-0 when the lock is used, thus hiding the user code from others.



- No keys to manage
- Code retrieval function
- 4 wheel code combination
- Up to 10,000 unique combinations
- Black powder coated finish
- Locked / unlocked indicators
- Available vertical and right hand
- Master Override Key available
- Private Function only
- Auto code scramble
- Suitable for indoor use only*
- Suitable for a panel thickness between 0.8mm - 22mm (¹/₃₂" - ⁷/₈")

BENEFITS

FUNCTIONS

The KL20 is only suitable for Private function ideal for personal storage lockers. The users can set their own 4 digit code and change this as often as they wish. With the addition of the override key, management can gain access and locate the user code.

AUTO ZERO / AUTO SCRAMBLE

When you lock or unlock the KL20 the dials automatically rest to 0-0-0-0 so the user code is hidden and cannot be inadvertently viewed.

FIXINGS

The KL20 is provided with a straight cam, back plate(s) and fixing screws as standard. An additional backplate and cranked cam are available to purchase separately.

CODE RETRIEVAL


Use the Master Override Key to open the lock, then hold down the code retrieval leaver and rotate the dials until they stop. This is your code.

PRICING

Prices below are list price.

ITEM	GBP	USD	EUR	
KL20 Mechanical KitLock	£35.00	\$45.00	€40.00	\$62.00

PRODUCT DIMENSIONS





TECHNICAL SPECIFICATION

FEATURE	DESCRIPTION
Functions	Private function only
Housing	Zinc Alloy front - plastic rear
Code Length	4 digit
Code Storage	Single code
Suitable For	Internal applications only*
Spindle Length	Fixed spindle suitable for panel thickness 0.8mm - 22mm (1/32" - 7/8")
Handing	Vertical and right hand
Door Prep	83mm x 27mm (3 ¹ / ₄ " - 1 ¹ / ₁₆ ")
Indicators	Locked (red) / unlocked (green)
Fixings	Back plate(s) and cam supplied Additional back plate and cam available
Cam	44.7mm (1 ⁹ / ₄ ") straight cam supplied 50mm (2") crank cam available separately

^{*}Not suitable for chlorine environments