

MRX-A Specifications



Mechanical Specifications

Application	For facilities housing patients in risk
Door Thickness	1-3/4" standard, other upon request
Backset	2-3/4"
Handing	Handed
Function	Refer to Function Sheet
Finish	630
Cover Plate	Stainless Steel, 7-1/2" x 2-3/4" x 1/2"
Arch Lever	Stainless steel
Thumb Turn	Stainless steel, ligature resistant, ADA compliant standard
Faceplate	Stainless steel, 1-1/4" x 8"
Strike	Stainless steel, ASA, 1-1/4" x 4-7/8"
Mounting	Through-bolt, tamper resistant mounting screws, for wood and metal door
Cylinder Specifications	Brass with stainless steel cover, 6pin, Schlage® "C" keyway standard, 2 keys per cylinder Small format IC with or without core, 6 or 7 pin core Schlage® Large Format IC less core available Corbin® Large Format IC less core available, for 6 pin core High Security Cylinder available, 6 pin, TownSteel "L" keyway High Security SFIC Core available, 7 pin, TownSteel "L" keyway
Warranty	5 year limited

Code Compliance

ANSI/BHMA	A156.13-2012 Grade 1 Certified
UL/ULC	UL 10C listed 3-hour rating
BAA	Meets requirements of the the Buy American Act
ADA	Meets requirements of the Americans with Disabilities act