

# **Wireless Alert System**

### RA-4961-K1Q Wireless Receiver and Wireless Pushbutton

The RA-4961-K1Q Wireless Alert System can be synced with a wide variety of wireless devices to suit almost any situation.

#### **Features:**

- Up to 1,000ft (305m) transmission range\*
- 18 Programmable ringtones
- Connect up to 4 wireless transmitter accessories
- Audible and visual alert via built-in speaker and flashing light
- Wall or desktop mountable
- Output terminals for optional auxiliary device
- Each channel independently programmable
- Includes Wireless Receiver (RA-4961Q) and Wireless Pushbutton (RA-4961-PBQ)





## RA-4961-VPQ Wireless Vibrating Receiver

The RA-4961-VPQ Wireless Vibrating Receiver has similar functions as the RA-4961Q Wireless Receiver, but is small enough to clip onto a belt.

#### Features:

- Audible, visual and physical alert via built-in speaker, LEDs and vibration
- Belt clip and small size for easy portability
- Size is only  $3^{9}/_{16}$ "x $2^{9}/_{16}$ "x $1^{1}/_{16}$ " and weight is only 2.7-oz.
- Each channel independently programmable

## RA-4961-PBQ Wireless Pushbutton

#### Features:

- For use with the RA-4961 series receivers Up
- Use as a wireless doorbell
- Up to 1,000ft (305m) transmission range\*
- Easy installation

<sup>\*</sup> Line of sight. Transmission range will vary depending on installation and operating environment.



16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: www.seco-larm.com Email: sales@seco-larm.com







## **Wireless Alert System**

## RA-4961-MCQ Wireless Magnetic Contact

#### Features:

- For use with the RA-4961 series receivers
- Wirelessly monitor windows, doors, or other areas
- Up to 1,000ft (305m) transmission range\*
- Activates each time the door or window is moved
- Magnet can be placed on either side
- Adhesive mount no screws required



#### RA-4961-MBQ Wireless Mailbox/Tilt Sensor

#### Features:

- For use with the RA-4961 series receivers
- Wirelessly monitor mailboxes or any tilting motion
- Up to 1,000ft (305m) transmission range\*
- Mounts to standard mailbox flaps or other flat surfaces that may tilt
- Adhesive mount no screws required
- Adjustable sensing angle



### RA-4961-DSQ Wireless Outdoor PIR Sensor

#### **Features:**

- For use with RA-4961 series receivers
- Wirelessly monitor driveways, walkways or other areas
- Up to 1,000ft (305m) transmission range\*
- Programmable activation time
- Programmable sensing range up to 39ft (12m)
- Runs on batteries for a convenient, wireless installation
- Adjustable mounting angle



## RA-4961-PRQ Wireless Indoor PIR Sensor

#### Features:

- For use with the RA-4961 series receivers
- Wirelessly monitor entryways, rooms, or other areas
- Up to 1,000ft (305m) transmission range\*
- Sensing range up to 26ft (8m)

- Programmable activation time
- Runs on batteries for a convenient, wireless installation
- Adjustable mounting angle



\* Line of sight. Transmission range will vary depending on installation and operating environment.

#### SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

**Phone**: (949) 261-2999 | (800) 662-0800 **Fax**: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

