L@C(LY GUARD™ DEFENDER (238L) | Lever Edition







Defender (238L) provides main entrance level access and security innovation beyond the front door. Ideal for storefront framed entry and exit doors.

Features

Hack-proof PIN Genie® digital touchscreen.

3D biometric fingerprint sensor access - stores up to 99 fingerprints.

Remote lock and unlock using the Lockly app.

Suitable for swing and sliding doors with narrow wood aluminum or broken bridge frames.

Built-in micro USB charging port for back up emergency access.

IPX5 rated for water protection.

Issue Offline Access Codes[™] that do not require users to download an app or have WiFi or Internet connection to use.

Fast pass MIFARE RFID Access.

eKeys - grant one-time use or specific time duration access by issuing codes or digital eKeys via a mobile device.

Grant access, even when you're not home - Remotely lock and unlock your door from anywhere using the Lockly app.


Full control with smartphone and Lockly\OS™.














L@C〈LY GUARD[™] **DEFENDER** (238L) | Lever Edition

Securely lock and unlock sliding and swing-style doors







Deadbolt for Swing Door

1 ¹/₈" (28.6mm) 1 ¹/₂" (38mm) ³¹/₃₂"(24.6mm)



Hook Bolt for Slide door

1 ¹/₈" (28.6mm) 1 ¹/₂" (38mm) ³¹/₃₂"(24.6mm)



(Optional) Push to Exit Bar for Swing Door

Fits wood, metal, or aluminum glass doors with a minimum sash width of $1 \frac{3}{4}$ (44.5mm).

Included

Defender Lever Edition smart lock Mortise Lockset assembly Secure Link Wifi Hub Wireless Door Sensor Installation Screws Strike Plate & Housing Back Plate Physical Keys x 5 AA Alkaline Batteries x 4 Quick Start Guide Installation and User Manuals MIFARE RFID Cards x 3

Works with Exit Push Bar, Push Pedal, Push Lever or another Defender (238L)

Specs

Deadlatch for

Swing Door

1 ¹/₈" (28.6mm)

 $^{31}/_{32}$ "(24.6mm)

 $1^{1}/_{2}$ " (38mm)

Function: Mortise Entry-Exit Smart Lock
Fit: door frames 2" - 3" (25.4mm - 76.2mm)
Door handle: field reversible for L/R swing doors
Dimensions (HxW):17 1/4 x 1 47/64" (438mm x 44mm)

Backset: 1" (25.4mm) Latch: ½" (12.7mm) steel Power Supply: AA x 4

Working environment: 4 ~ 140°F (-20 ~ 60°C) **Colors**: Stainless Steel and Matte Black



STAINLESS STEEL



MATTE BLACK

Requirements

Free Lockly app for iOS or Android

Door frame thickness: 1" - 2 1/4" (25.4mm - 54mm) **Door frame width:** 2" - 3 " (50.8mm - 76.2mm)



For more information, please visit: www.locklyPro.com

