

DO-IT-YOURSELF INSTRUCTIONS FOR INSTALLATION OF SINGLE AND DOUBLE CYLINDER DEADLOCKS OR THE REPLACEMENT OF EXISTING LOCKS.

TOOLS REQUIRED FOR REMODELING OR NEW CONSTRUCTION:

- 1 phillips head screwdriver
- 1 2" hole saw
- 1 1" drill
- 1 chisel

TOOLS REQUIRED FOR REPLACEMENT:


- 1 phillips head screwdriver

FOLLOW STEPS 3c, 4, 5 and 6b FOR DO-IT-YOURSELF REPLACEMENT, FOLLOWING REMOVAL OF EXISTING LOCK.

REPLACING EXISTING DEADLOCKS:

Before beginning, measure from center of lock to door edge in order to check length of backset on existing lock to that of new lock. The backset length is stated clearly on front of package. If backset size is the same, continue; otherwise, you'll have to replace lock with proper size lock and backset.

INSTRUCTION FOR ADJUSTABLE DEADBOLT




TO CHANGE 2-3/8" TO 2-3/4"


Thumb press the end of the latch, with the Adjustable Slot facing toward yourself, turn the body of the latch clockwise and make sure that **THE PIN DROP INTO THE SECONDARY SLOT, THEN PULL TO THE SIDE**. Twist the body of the latch counterclockwise **TILL THE PIN DROP INTO THE UPPER PRIMARY SLOT**.

60mm(2-3/8 ")
70mm(2-3/4 ")

1. MARK DOOR




A. Fold and apply template to high edge of door bevel and mark center of door edge as indicated on template at the desired height from the floor.




B. Mark center hole on door face through guide on template. For either 2 3/8", 2 3/4" backset.

2. DRILL HOLES




A. Drill thru door face as marked for lockset: It is recommended that holes be drilled from both sides to prevent splitting. Hole size is 2" for standard installations.




B. Drill 1" hole in center of door edge thru to 2" hole for latch.


3. INSTALL LATCH



A. Insert latch in hole, keeping it parallel to face of door. Mark outline and remove latch.



B. Chisel 1/8" deep or until latch face is flush with door edge.



C. Install deadbolt latch in "up" position into hole as shown on latch. Insert and tighten screws.