

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOLYKOTE(R) D-321 R ANTI-FRICTION COATING
Product code : 000000000001283341, 000000000001283341

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Lubricants and lubricant additives

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe

Manufacturer or supplier's details : 65091

Telephone : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163

E-mail address of person responsible for the SDS : sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350
Dow Corning (Wiesbaden 24h) Tél: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P331 Do NOT induce vomiting.

Hazardous components which must be listed on the label:

n-Butyl acetate

Naphtha (petroleum), hydrodesulfurized heavy

2.3 Other hazards

Static-accumulating flammable liquid.
Vapours may form explosive mixture with air.

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Inorganic and organic compounds
in mineral oil

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1 265-185-4	Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 30 - < 50
Polybutyl titanate	9022-96-2	Flam. Liq. 3; H226 Eye Irrit. 2; H319	>= 10 - < 20
Butan-1-ol	71-36-3 200-751-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	>= 1 - < 3
Zinc oxide	1314-13-2 215-222-5 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.25 - < 1

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Sulphur oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing meth- : Use extinguishing measures that are appropriate to local cir-

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

ods
cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Ensure all equipment is electrically grounded before beginning transfer operations.
This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical igni-



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

tion source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations.
Restrict flow velocity in order to reduce the accumulation of static electricity.

- Local/Total ventilation : Use with local exhaust ventilation.
Use only in an area equipped with explosion proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapours or spray mist.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases

7.3 Specific end use(s)

- Specific use(s) : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may re-



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

quire added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
Molybdenum sulfide	1317-33-5	TWA	10 mg/m ³ (Molybdenum)	GB EH40
		STEL	20 mg/m ³ (Molybdenum)	GB EH40
Graphite	7782-42-5	TWA (inhalable dust)	10 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable dust)	4 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for			

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

	<p>sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
Butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	960 mg/m3
	Workers	Inhalation	Acute local effects	960 mg/m3
	Workers	Inhalation	Long-term systemic effects	480 mg/m3
	Workers	Inhalation	Long-term local effects	480 mg/m3
	Consumers	Inhalation	Acute systemic effects	859.7 mg/m3
	Consumers	Inhalation	Acute local effects	859.7 mg/m3
	Consumers	Inhalation	Long-term systemic effects	102.34 mg/m3
	Consumers	Inhalation	Long-term local effects	102.34 mg/m3

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Substance	Exposure	Route	Effects	Value
Graphite	Consumers	Inhalation	Long-term local effects	0.3 mg/m3
	Consumers	Ingestion	Long-term systemic effects	813 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	1.2 mg/m3
Butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3.125 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	55 mg/m3
Zinc oxide	Workers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0.83 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-Butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Intermittent use/release	0.36 mg/l
	Sewage treatment plant	35.6 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.0981 mg/kg
	Soil	0.0903 mg/kg
Butan-1-ol	Fresh water	0.082 mg/l
	Marine water	0.0082 mg/l
	Intermittent use/release	2.25 mg/l
	Sewage treatment plant	2476 mg/l
	Fresh water sediment	0.178 mg/kg



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
 Date of first issue: 18.11.2014

	Marine sediment	0.0178 mg/kg
	Soil	0.015 mg/kg
Zinc oxide	Fresh water	20.6 µg/l
	Marine water	6.1 µg/l
	Sewage treatment plant	52 µg/l
	Fresh water sediment	117.8 mg/kg
	Marine sediment	56.5 mg/kg
	Soil	35.6 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
 Minimize workplace exposure concentrations.
 Use only in an area equipped with explosion proof exhaust ventilation.
 Use with local exhaust ventilation.

Personal protective equipment

- Eye protection : Wear the following personal protective equipment:
Safety goggles

- Hand protection
 - Material : Antistatic gloves
Impervious gloves
Flame retardant gloves

 - Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

- Filter type : Combined particulates and organic vapour type (A-P)

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: dark grey
Odour	: solvent-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 100 °C
Flash point	: 23 °C Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 1.07
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: < 20.5 mm ² /s
Explosive properties	: Not explosive

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture
Handling operations that can promote accumulation of static charges.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Water

10.6 Hazardous decomposition products

Contact with water or humid air : Butan-1-ol

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Method: Calculation method

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 13.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Butan-1-ol:

- Acute oral toxicity : LD50 (Rat): 790 mg/kg
- Acute inhalation toxicity : LC0 (Rat): > 17.76 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rabbit): 3,430 mg/kg

Zinc oxide:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

- Species: Rabbit
- Method: OECD Test Guideline 404
- Result: No skin irritation
- Remarks: Based on data from similar materials
- Assessment: Repeated exposure may cause skin dryness or cracking.

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Butan-1-ol:

Species: Rabbit
Result: Skin irritation

Zinc oxide:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation
Remarks: Based on data from similar materials

Polybutyl titanate:

Result: Irritation to eyes, reversing within 21 days

Butan-1-ol:

Species: Rabbit
Method: OECD Test Guideline 405
Result: Irreversible effects on the eye

Zinc oxide:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Test Type: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

Butan-1-ol:

Test Type: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative

Zinc oxide:

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Test Type: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Butan-1-ol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Species: Rat
Application Route: inhalation (vapour)
Exposure time: 13 weeks
Result: negative
Remarks: Based on data from similar materials

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Butan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Hamster
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Assessment: May cause drowsiness or dizziness.

Butan-1-ol:

Assessment: May cause respiratory irritation.

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Target Organs: Central nervous system

Assessment: Causes damage to organs through prolonged or repeated exposure.

Zinc oxide:

Exposure routes: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Species: Rat

NOAEL: 2.34 mg/l

LOAEL: 4.67 mg/l

Application Route: inhalation (vapour)

Exposure time: 6 Months

Method: OECD Test Guideline 413

Remarks: Based on data from similar materials

Butan-1-ol:

Species: Rat

NOAEL: 125 mg/kg

Application Route: Ingestion

Exposure time: 13 Weeks

Zinc oxide:

Species: Rat

NOAEL: 1.5 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 3 Months

Method: OECD Test Guideline 413

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

|| regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

|| Inhalation : Target Organs: Central nervous system
 Symptoms: Dizziness, Headache, Neurological disorders

SECTION 12: Ecological information

12.1 Toxicity

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 10 - 30 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 10 - 22 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae	: EL50 (Pseudokirchneriella subcapitata (green algae)): 4.6 - 10 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	: NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR: 0.097 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Remarks: Based on data from similar materials

Butan-1-ol:

|| Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

**MOLYKOTE(R) D-321 R ANTI-FRICTION
COATING**

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1,328 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): 225 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
Toxicity to bacteria	: EC50 (Pseudomonas putida): 4,390 mg/l Exposure time: 17 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 4.1 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211
Zinc oxide:	
Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 330 - 780 µg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 6.9 - 16.2 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Selenastrum capricornutum (green algae)): 136 µg/l Exposure time: 72 h Method: OECD Test Guideline 201 NOEC (Selenastrum capricornutum (green algae)): 24 µg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	: 1
Toxicity to bacteria	: EC50 : 5.2 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	: NOEC: 199 µg/l Exposure time: 30 d Species: Oncorhynchus mykiss (rainbow trout) Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 37 µg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Remarks: Based on data from similar materials
M-Factor (Chronic aquatic toxicity)	: 1

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

II

12.2 Persistence and degradability

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Biodegradability : Result: Readily biodegradable
Biodegradation: 74.7 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Polybutyl titanate:

Biodegradability : Result: Not readily biodegradable.

Butan-1-ol:

Biodegradability : Result: Readily biodegradable
Biodegradation: 92 %
Exposure time: 20 d

12.3 Bioaccumulative potential

Components:

Naphtha (petroleum), hydrodesulfurized heavy:

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Based on data from similar materials

Butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1

Zinc oxide:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 177

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
Date of first issue: 18.11.2014

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not burn, or use a cutting torch on, the empty drum.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1993
ADR : UN 1993
RID : UN 1993
IMDG : UN 1993
IATA : UN 1993

14.2 UN proper shipping name

ADN : FLAMMABLE LIQUID, N.O.S.
(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
ADR : FLAMMABLE LIQUID, N.O.S.
(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
RID : FLAMMABLE LIQUID, N.O.S.
(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
IMDG : FLAMMABLE LIQUID, N.O.S.
(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy, Zinc oxide)
IATA : Flammable liquid, n.o.s.
(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information



MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version 3.0 Revision Date: 02.11.2015 SDS Number: 774946-00006 Date of last issue: 30.10.2015
 Date of first issue: 18.11.2014

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t
----	---	---------	----------

Other regulations : Take note of Dir 94/33/EC on the protection of young people at work.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

	exempted from listing on the TSCA Inventory of Chemical Substances.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
KECI	: All ingredients listed, exempt or notified.
PICCS	: All ingredients listed or exempt.
REACH	: All ingredients (pre-)registered or exempt.
ENCS/ISHL	: Some components are not listed or not identified on ENCS/ISHL.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
TCSI	: All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H372	: Causes damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Acute aquatic toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

MOLYKOTE(R) D-321 R ANTI-FRICTION COATING

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, un-

**MOLYKOTE(R) D-321 R ANTI-FRICTION
COATING**

Version	Revision Date:	SDS Number:	Date of last issue: 30.10.2015
3.0	02.11.2015	774946-00006	Date of first issue: 18.11.2014

less specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN