Rotary Screw Air Compressors RK 5HP-10HP VSD - Belt Drive Series



Features & Benefits **RK 5HP-10HP VSD Belt Drive Series Rotary Screw** Air Compressor

Same Features & Benefits of Larger VSD Units



Variable **Frequency** Drive Inverter


Unlimited Motor Starts per Hour

No inrush current to overheat the motor

Consistent Discharge Pressure

- Setting 'target' pressure instead of load/unload setpoints
- Consistent pressure means consistent production results

Efficiency Load Comparison



Variable Speed Drive Intake Modulation **Geometry Control**



Up to 85% Turn-Down

The inverter runs the compressor at 15-100% capacity to meet current demand

Soft Motor Starts

- Eliminaes slow motor starts
- Significantly lowers electricity demand
- Does not allow full voltage motor starts as with fixed speed

Reduced Power Consumption

KW consumption is directly tied to compressed air demand resulting in significant energy savings

Available as Tank Mounted and with Integrated Dryer

Also Available in Low Voltage **Configurations**



Electronic Controller



Pressure Parameters

Set target pressure to match your exact demand

Cooling Fan Control

Controls the air/oil cooling fan based on actual oil temperature conditions - Fan cycles only when needed

Alarm Conditions/Reset

Past and current alarms are recorded, allowing for quick diagnosis

Current Duty Cycle

Monitors the demand on the compressor

Maintenance Timers

Track and set your maintenance schedule

Discharge Pressure

Displays current air discharge pressure

Oil Temperature

Protects against overheating by allowing this critical temperature to be easily monitored

Phase Monitor

Prevents reverse rotation and protects against power loss damage

RK 5HP-10HP Specifications

MM SIII IOIII SPECIJICACIONS										
Model	Dryer Included	HP	kW	CFM	PSI	dBA (gal)	Tank (3ph)	Voltage (LxWxH)	Dimensions (in) (lbs)	Weight
RK-5VSD-145B	No	5	4	20	145	66	-	460	30 x 24 x 25	375
RK-5VSD-145B-L	No	5	4	20	145	66	-	200/230	30 x 24 x 25	375
RK-7.5VSD-115T	No	7.5	5	28.4	115	66	71	460	59 x 24 x 58	748
RK-7.5VSD-115T-L	No	7.5	5	28.4	115	66	71	200/230	59 x 24 x 58	748
RK-7.5VSD-115T-D	Yes	7.5	5	28.4	115	66	71	460	59 x 24 x 58	788
RK-7.5VSD-115T-D-L	Yes	7.5	5	28.4	115	66	71	200/230	59 x 24 x 58	788
RK-10VSD-115T	No	10	7	39.8	115	67	71	460	59 x 24 x 58	748
RK-10VSD-115T-L	No	10	7	39.8	115	67	71	200/230	59 x 24 x 58	748
RK-10VSD-115T-D	Yes	10	7	39.8	115	67	71	460	59 x 24 x 58	788
RK-10VSD-115T-D-L	Yes	10	7	39.8	115	67	71	200/230	59 x 24 x 58	788

5 Year Pneu-Assure Warranty

Industry-Leading Peace-of-Mind

5 Year Warranty on Major Components*

Air End

Oil Sump Tank

Electric Motor(s)

Air Cooler

Oil Cooler

VSD Unit

1 Year Warranty on the Entire Unit

Regular maintenance NOT included

✓ Guaranteed Support

From Your Certified Distributor

Technical Expertise

Industry-leading knowledge & experience

^{*}Warranty subject to change based on region and distributor's agreement. 5-Year Warranty on Master Components requires the use of Genuine PneuTech Parts & Compressor Oil.

Our Mission Statement

Using our combined industry experience, we provide knowledge, support, and superior products to compressed air distributors across the globe.

We are committed to producing positive results through being trustworthy, ethical, and accessible.

We are founded in the beliefs that through working together we can continue to transform the industry, while rising to turn challenges into opportunities.



United States | United Kingdom | New Zealand

WSI Machinery

1530 N. Old Rand Road Wauconda, IL 60084 847.526.1411 www.wsimachinery.com PT-118-Rev3

