

CANTEK

CM626

26" PLANER



CM626 | 26" PLANER

Powerful 26" heavy duty planer that fits your everyday needs.

The Cantek CM626 26" Planer is a production planer with high horsepower and feed rates. It is equipped with our spiral insert knife cutterhead with two sided replaceable knives which produce a smooth planed finish with maximum cutting depth. With upper and lower driven feed rollers the CM626 can plane even the most difficult to feed material. The powerful 20HP motor can ensure optimum stock removal even on full width boards. With infinitely variable feeds the operator has full control to ensure the optimum feed speed according to your needs. Equipped with motorized movement of the table by convenient digital control the operator can accurately input the desired thickness to achieve accurate results.



Rear side of machine



Cast iron planer assembly with sectional chipbreakers and spiral insert knife cutterhead



Operator controls with digital thickness control unit



Adjustable infeed and outfeed bed rolls



Bed rolls



Variable feed speed and micro table height adjustment controls



Powerful chain driven upper and lower rollers and variable speed feed motor

Key Advantages.

- Spiral insert knife cutterhead with superior cut quality and maximum depth of cut
- Two-sided solid carbide inserts are easily changed while providing optimum wear life
- Heavy-duty cast iron machine frame ensures long machine life, optimum cut quality with its superior vibrating damping properties
- Driven bed rollers for optimum feeding results even with difficult to feed material
- Powerful 20HP cutterhead motor for even the most demanding planing jobs
- Digital thickness control for accurate automatic adjustment of the table position
- Serrated sectional infeed roll, sectional chip breakers and pressure shoes
- Driven opposing upper and lower feed rollers for optimum feeding results
- Variable feed speed to 70 FPM
- Adjustable bed rollers to assist feeding results when required
- Anti-kickback fingers ensure safe operation
- Heavy duty elevation jack screws and precision machined slides for accurate and smooth table movement
- Sound dampening machine cover conveniently hinges to provide easy access to the planer head and feed assembly
- 6" dust port

Specifications.

Maximum planing width	26"
Maximum planing thickness	11.8"
Minimum planing thickness	0.15" (4mm)
Maximum depth of cut	0.31" (8mm)
Minimum planing length	10.35" (263mm)
Table area	35" x 27"
Feed speeds variable	23~98 FPM
Main motor	20 HP
Feed motor	1 HP
Table motor	1/2 HP
Knives	30 x 12 x 1.5mm
Cutterhead diameter	4 3/4"
Cutterhead RPM	5000 RPM
Top feed rollers	3" dia.
Dust hood outlet	6" dia.
Machine weight	2200 lbs.
Machine dimensions (WxDxH)	46"x39"x49"