





FEATURES

- 5 HP main motor with 1HP scoring motor
- 10' precision anodized aluminum sliding table travels on ball bearings which run on hardened steel guide strips
- 14" maximum main blade diameter
- · Solid cast iron main table which is precision ground
- Solid rip fence runs on precision round cylindrical guide and is equipped with manual fine adjustment and locking lever
- 51" rip capacity
- · Optional overhead saw blade guard included (CE-type) with built in dust port
- Manual blade rise / fall& tilting with blade angle indicator
- Convenient manual scoring adjustment
- · Eccentric hold down clamp & wedge for solid wood ripping included
- Extendable outrigger arm supports crosscut fence assembly
- · Aluminum extruded crosscut fence with two flip stops with dual metric and inch rulers
- Available in 3-phase and 1-phase electrics

SPECIFICATIONS

PMB #104 1124 Fir Avenue

Blaine, WA 98230

Cast iron fixed table dimension	1500 x 1726 mm (59" x 68")
Sliding table dimension	3200 x 360 mm (10ft. x 14")
Max. main saw blade diameter	305 / 355 mm Max
Main saw bore	30 mm
Max. cutting height with blade at 90°	90 / 115 mm
Max. cutting height with blade at 45°	63 / 81 mm
Main motor power	5 HP
Main blade speed	4000 RPM
Scoring saw blade	120 mm (4.7")
Scoring saw blade bore	20 mm
Scoring blade motor power	1 HP
Scoring blade speed	8000 RPM
Blade tilt	$0 - 45^{\circ}$
Max. ripping width	1300 mm (51")
Dust collection ports	(1) 100 mm (3.9") / (1) 60 mm (2.3")
Machine weight	990 lbs. (450 kgs)
Machine shipping weight	1210 lbs. (550 kgs)
Sliding table weight	176 lbs. (80 kgs)







T: 1.888.982.2683 F: 604.540.1780 Youtube // @CantekMachinery
Twitter // @CantekMachinery

