

# BRAVO® LE/VE MODEL

## Specifications

**Unless Specifically Noted, Specifications refer to both LE and VE Models.**

**Overall Dimensions:** Bravo LE – 55.75”L (141.6 cm) x 45.5” W (116 cm) x 56” H (142 cm)

Bravo VE – 55.75”L (141.6 cm) x 45.5”W (116 cm) x 52”H (132 cm) – Refer to Installation Drawings for additional details.

**Dimensions Seat to Floor:** 24” (61 cm)

**Suggested Minimum Distance from Back Edge of Spa Base to Back Wall:** Bravo LE – 19” (48 cm) Bravo VE – 22” (56 cm)

Refer to Installation Drawings for additional details.

**Shipping Dimensions Including Skid:** 68” L (173 cm) x 34” W (86 cm) x 44” H (112 cm)

**Shipping Weight Including Skid:** Bravo LE – 315 lbs. (143 kg) / Bravo VE – 338 lbs. (153 kg)

**Shipping Dimensions (Carton Size):** 84.0” L (213 cm) x 40.0” W (102 cm) x 44” H (112 cm)

**Net Weight:** Bravo LE – 290 lbs. (132 kg) / Bravo VE – 313 lbs. (142 kg)

**Client Weight Capacity:** 350 lbs. (160 kg)

**Basin Capacity:** 4.75 US Gallons (18 liters)

**Power Requirements:** 120V AC, 15 Amp, 60HZ. A separate and dedicated 15 Amp GFCI circuit MUST be used for each pedicure chair.

**Construction:** Reinforced fiberglass with chemical resistant gel-coated finish.

**Basin:** Specially hardened and tempered glass, pre-plumbed.

**Jet System:** One (1) Dual Stream Magnetic Jet. Optional I-Fill® system (automatically fills and shuts-off) is available.

**IMPORTANT: Your Pedicure Chair MUST be Installed by a Licensed Electrician and a Licensed Plumber in Accordance with all National, State and Local Codes/Regulations.**

### **PLUMBING:**

**Incoming:** Hot/Cold supply lines required (1/2” ID). 1/2” MPT connections located on back of spa base.

**Sprayer/Filler:** Inline back-flow prevention is provided.

**Discharge:** Gravity drain is standard. Optional factory installed drain pump (air activated switch) with a 3/4” MPT connection located on back of spa base. Back flow prevention is provided.

**MASSAGE:** Full Function Shiatsu Back Massage with fold down manicure trays and hand held control wand.

**CHAIR CONTROLS:** Two (2) linear actuators electronically controlled with hand held wand. Forward/Backward/Recline.

Certification: Underwriters Laboratories Listed  Compliance Listings to the following Standards: UL 1951, CAN/CSA C22.2 No. 68-92, ANSI/ASME A112.18.3M, A112.19.7M, A112.18.1, CSA B125.1.2005

Compliant with IAPMO Plumbing Standards. Fixtures and hoses are UPC compliant.

**LIMITED WARRANTY:** Please refer to **Limited Warranty** in Owner’s Manual. Visit our website and MyContinuumPedicure.com.

### **ACCESSORIES:**

**Deluxe Tech Chair:** Base: 19” diameter (48 cm) Height range (excluding cushion): 12” to 15” (30.5 cm to 38 cm)

Net weight: 15 lbs. (7 kg)

**Shipping Dimensions:** 26” W (66 cm) x 26” L (66 cm) x 12” H (31 cm) Shipping Weight: 23 lbs. (11 kg)

**Standard Tech Chair:** Base: 18” diameter (46 cm) Height range (including cushion): 12” to 18” (30.5 cm to 38 cm)

Net weight: 13 lbs. (6 kg)

**Shipping Dimensions:** 22” W (56 cm) x 30” L (76 cm) x 10” H (25 cm) Shipping Weight: 15 lbs. (7 kg)

**Accessory Cart:** 16” L (40.6 cm) x 13” W (33 cm) x 17” H (43 cm)-Height is from floor to working surface. Net Weight: 28 lbs. (12.5 kg)

**Shipping Dimensions:** 21” W (53 cm) x 19” L (48 cm) x 23” H (58 cm) Shipping Weight: 37 lbs. (16.5 kg)

**Note: Due to continuous improvements, all specifications are subject to change without notice. All dimensions and weights are approximate.**