



# Hil o MultiPro

## EVOLVING THE SPA EXPERIENCE

#### TOP:

Four-piece adjustable top with round corners, three-layer foam, 3/4" plywood Top design

Standard size top 30" x 73"

2" firm bottom layer + 1- 3/4" medium-density layer of urethane polymer Foam

Polyester batting 1/2" fluffy polyester Dacron top layer

Frame 3/4" plywood frame reinforced for arm rests and face cradle

Manual, paddle-release adjustment of knee and upper-body sections Adjustments

Back tilt angle 0 to 80° Knee tilt angle 0 to 30°



Sleek, contemporary design with white powder-coat finish Carbon steel base

8" recess from ends of table 8" leg recess

Height range - standard 19" to 34" infinite motorized adjustment

Lifting weight capacity 450 lbs.; static weight capacity 500 lbs. Weight capacity

#### **MOTORS & CONTROLS:**

One 24v DC, 5 amp max motor/actuator, UL recognized, powered through a Base lift motor

110v, 5 amp transformer

Foot control for lift motor Controls

#### VINYL:

UltraSoft-Touch - standard Lightly textured, super-soft PU vinyl, fabric backed

### **OPTIONAL ACCESSORIES:**

Flex Armrests Armrests Contour FaceSpace Face support

Foot extension Salon Footrest or Full Footrest

Neck Bolster Facial Neck Bolster

## **GUARANTEES:**

10 yr. on replacement parts for frame/structure and 1 yr. on labor\*\* Structure

Motor & controls 2 yr. warranty on materials for mechanical/electrical parts

Vinyl & foam 2 yrs. on materials


\*\*Labor warranty for USA customers only


### **WEIGHTS:**


10/20/2016


Table weight 210 lbs. 250 lbs.

Shipping weight - boxed









www.TouchAmerica.com (800) 678-6824 - (919) 732-6968