

CAT NETTING WITH REINFORCED WEBBING



One of our most popular netting options is our professionally pre-made cat nets. These products are pre-made ¾" nets with professionally sewn reinforced webbing edging. The webbing adds a professional touch to your installation, and gives added strength to your net. It is perfect for verandahs, patios & side alleys. The webbing is pre-installed along the top and bottom (long sides) and can be cut off if not required.

Features:

- ☞ Transparency 87%
- ☞ Reinforced webbing top & bottom (along the long side)
- ☞ Unobtrusive netting / thin net twine
- ☞ Pre-Stretched - will not sag or stretch over time
- ☞ 19mm x 19mm Mesh Size
- ☞ Knotted High Density Polyethylene material
- ☞ Low-Vis Black or Stone/Beige
- ☞ Heat strengthened knots
- ☞ Will not fray or unravel when cut to size
- ☞ 21.61 KGF B/S per strand
- ☞ 0.2% UV Treated (See below for accredited test)

The original Catnets netting, our low-vis ¾" is used throughout residential and commercial cat enclosures Australia wide. Our ¾" netting is also supplied throughout New Zealand and The United States. Our ¾" x ¾" netting is UV treated, Pre-Stretched and has heatstrengthened knots.

Supplied for over 1000 enclosures each year, this netting is available in a variety of pre-made sizes.

Our netting manufacturer is certified to:



Our netting is the chosen product of over 25 installers & resellers throughout Australia & N.Z



UV TEST RESULTS

Netting Specification:

500Denier / 9ply HDPE
Black Colour
Mesh Size: $\frac{3}{4}$ " x $\frac{3}{4}$ "

Testing Method:

QUV ACCELERATED WEATHERING TESTER
IS 16008:Part2

Results:

3 years Equivalent to outdoor Exposure: 98% Strength maintained (2% loss)

5 years Equivalent to outdoor Exposure: 96% Strength maintained (3.3% loss)

10 years Equivalent to outdoor Exposure: 93% Strength maintained (6.6% loss)

Notes on UV testing

The QUV accelerated weathering tester reproduces the damage caused by sunlight, rain and dew. In a short period of time, the QUV UV tester can reproduce the damage that occurs over months or years outdoors. To simulate outdoor weathering, the QUV accelerated tester exposes materials to alternating cycles of UV light and moisture at controlled, elevated temperatures. It simulates the effects of sunlight using special fluorescent UV lamps. It simulates dew and rain with condensing humidity and/or water spray. With thousands of testers in use worldwide, it is the world's most widely used weathering tester. UV light is responsible for almost all photodegradation of durable materials exposed outdoors. The QUV tester's fluorescent lamps simulate the critical short-wave UV and realistically reproduce the physical property damage caused by sunlight. Types of damage include color change, gloss loss, chalking, cracking, crazing, hazing, blistering, embrittlement, strength loss and oxidation.