
# **Cotton Tipped Applicator**

Wood handle



## Description

This absorbent cotton tipped applicator is produced with High Quality USP grade cotton which is carded and coiled onsite to maintain consistency. It is bonded securely to a rigid white birch handle by an aqueous based adhesive.

### **Dimensions**

# 6" Overall Length (76.2 mm)

#### qiT

- 0.188" Dia. (4.78mm)
- 0.625" Length (15.88 mm)

#### Handle

- 0.100" Dia. (2.54 mm)
- 5.812" Length (147.62 mm)

## **Qualities**

- · Medical grade quality
- Absorbent tip
- · Soft smooth tip
- Made in USA

## **Applications**

- · Applying salves or ointments
- · Wound care
- · Application of topical dressings
- Specimen colleciton
- Applying adhesives or other liquids
- · Removing dirt, contamination, fluxes or resins
- · Cleaning with IPA or other solvents

Ref #	Packaging
806-WC Non-sterile	<b>10/10/100</b> (10 boxes per case, 100 bags per box, 100 swabs per bag)



Tel 800 321-2313 (US & Canada Only) or 207-876-3311

Web puritanmedproducts.com Email sales@puritanmedproducts.com



# **Cotton Tipped Applicator**

Wood handle

Ref #: 806-WC

**NVR** 

**NON-VOLATILE RESIDUE** Test method: IDEMA method M7-98

**NVR Solvent - Hexane** 

NVR 12 µg/swab

The minimum detection limit for NVR is 10 µg/swab

## ION CHROMATOGRAPHY TESTING RESULTS

**IONIC CLEANLINESS** Test method: IDEMA M13-99 (anions) M12-99 (cations)

Anions

Floride ND

Chloride 0.9000 µg/swab

Nitrate

Bromide 2.5000 µg/swab Nitrate 0.3250 µg/swab Sulfate 4.3000 µg/swab Phosphate 11.2500 µg/swab

Cations

Lithium ND

Sodium 10.8000 µg/swab ND - Non Detected

0.7500 µg/swab Ammonium Potassium 13.7550 µg/swab Test procedures available upon request.

2.7450 µg/swab Magnesium Calcium

6.8250 µg/swab



Puritan Medical Products Company LLC Guilford, Maine 04443-0149 USA ISO 9001 2008 ISO 13485:2003 C€

Tel 800 321-2313 (US & Canada Only) or 207-876-3311

Web puritanmedproducts.com Email sales@puritanmedproducts.com