

16' SAN JUAN DORY LUMBER ORDER

ITEM	MATERIAL	SIZE	QUANTITY
Topsides	Okoume Ply	6mm	4
Bottom	Okoume or Mahogany Ply	9mm	2
Transom	Okoume Ply	9mm	1
Bulkheads	Okoume Ply	9mm	1
Splashwell	Bottom & transom scrap		
Seat tops	Okoume Ply	12mm	1
Frames	CVG Fir or Mahogany	4/4 X 4 X R	24 lineal ft.
Frames	CVG Fir or Mahogany	4/4 X 6 X R	30 lineal ft.
Chines	CVG Fir	4/4 X 4 X 16'	1 pc.
Spray rails	CVG Fir	8/4 X 4 X 16'	1 pc.
Guards	Appropriate hardwood	4/4 X 6 X 10'	2 pcs.
Inwales	Same as guards	4/4 X 6 X 16'	1 pc.
Stem and forefoot	Mahogany	8/4 X 7 X 4'	1pc.
Floorboards	1 X 4 CVG finish fir	3/4 X 3-1/2	110 lineal ft.
Chine guards	Mahogany or oak	4/4 X 4 X 14'	1 pc.
Skeg	Oak	8/4 X 2 X 12'	1 pc.
Bottom skids	Oak	4/4 X 6 X 12'	1 pc.

Notes:

Your local woods can be substituted. You can use Fir Marine plywood in place of the hardwood plywoods indicated.

6mm = 1/4"; 9mm = 3/8"; 12mm = 2"

8/4 means 2" rough lumber

4/4 means 1" rough lumber

"R" means random lengths