



## MK7.5 GTI Front License Plate Installation Instructions

### Kit contents:

- (1) Main Front Plate
- (4) Retention Brackets
- (4) Flat head 8-32 x 2" Stainless Screws
- (4) Flanged Stainless M5x10 License Plate Mounting Screws

1. The kit is specifically designed to be mounted in a precise location on the MK7.5 GTI grill. Mounting it in any other location will cause it not to fit properly. There are 4 retention brackets which are all identical so it doesn't matter which you use in each location. The locations to insert the brackets are show here.



2. All the retention brackets are installed in the same manner. Hold the retention bracket in your hand like so.



3. Insert the retention bracket into one of the specified locations as shown in step #1.



4. Once the retention bracket is sitting in the hole, rotate the bracket until it clips into place. I suggest using your thumb to push while pulling it forward with your pointer finger.



5. With all four retention clips installed it should look like this.



6. Position the main front plate over the retention brackets aligning the holes in the front plate with the copper screw inserts. Starting with the hole in the 10 o'clock position, hand thread one of the 8-32 x 2" flat head screw in while looking at through the cutout in the plate. Make sure that the screw is threaded on straight and not cross threaded. Do not tighten this screw at this time.



7. Next hand thread on the screw at the 4 o'clock position while viewing the alignment from the right side of the plate. Make sure that the screw is threaded on straight and not cross threaded. Do not tighten at this time.



8. Now hand thread on the remaining two screws again taking care not to cross thread them. Once all 4 screws are hand threaded on use a #2 Phillips screw driver to tighten the screws. Tighten all 4 screws evenly until the main front plate sits securely on the grill and the foam padding on the back is slightly compressed. **\*Do not over tighten the screws as doing so may damage the main front plate or the grill.**



9. The main front plate has three sets of holes to position the license plate to your preference. Use a 3mm hex key to secure the license plate mounting screws. Utilizing the farthest outside holes will not block the intercooler and allow for the best performance. Do not over tighten the license plate screws, all you need to do is to bottom out the screw head on the license plate. In the event that you overtighten the screw enough and happen to strip the hole then remove the screw and apply a light coat of super glue inside the hole and allow to dry before installing the screw.

