

Action	ON-OFF-(ON)	(ON)-OFF-(ON)	OFF-ON	OFF-(ON)	ON-OFF-ON	(ON)-OFF-ON	(ON)-OFF-(ON)
Pole / Throw	SPDT	SPDT	DPST	DPST	DPDT	DPDT	DPDT
Actuator Color	Gray - Contura III						
Common Applications	bilge pumps	labeled dimmer	navigational lights	horn or wind-shield wipers	combining nav lights or anchor light with shared bulb	dual wipers	power operated hatches
Maximum Amperage	15A @ 24V DC	15A @ 24V	15A @ 24V	15A @ 24V	15A @ 24V	15A @ 24V	15A @ 24V
	20A @ 12V DC	20A @ 12V	20A @ 12V	20A @ 12V	20A @ 12V	20A @ 12V	20A @ 12V
Amperage Operating Current	18mA (LED)		18mA (LED)	18mA (LED)	18mA (LED)	18mA (LED)	18mA (LED)
Minimum Operating Temperature	-40° C	-40° C	-40° C	-40° C	-40° C	-40° C	-40° C
Maximum Operating Temperature	85° C	85° C	85° C	85° C	85° C	85° C	85° C
Actuator Position to Light LED	(ON)		ON		ON	ON	
Embedded LEDs	1		1	0	2	1	0
Lighting	LED rated 100,000 hours half-life						
Seals	Internal and external gasket panel seal						
Weight			0.09Lb	0.09Lb	0.09Lb	0.09Lb	0.09Lb

Action	OFF-ON	OFF-(ON)	ON-OFF-ON	(ON)-OFF-ON	(ON)-OFF-(ON)	ON-ON
Pole / Throw	SPST	SPST	SPDT	SPDT	SPDT	DPDT
Actuator Color	Gray - Contura III					
Common Applications	lights	horn or wind-shield wipers	combining nav lights or anchor light with independent bulbs	bilge pumps	windlass, trim tabs, and powered hatches	switching between shunts or current transformers with one meter
Maximum Amperage	15A @ 24V	15A @ 24V	15A @ 24V	15A @ 24V	15A @ 24V	15A @ 24V
	20A @ 12V	20A @ 12V	20A @ 12V	20A @ 12V	20A @ 12V	20A @ 12V
Amperage Operating Current	18mA (LED)	18mA (LED)	18mA (LED)	18mA (LED)	18mA (LED)	18mA (LED)
Minimum Operating Temperature	-40° C	-40° C	-40° C	-40° C	-40° C	-40° C
Maximum Operating Temperature	85° C	85° C	85° C	85° C	85° C	85° C
Actuator Position to Light LED	ON		ON	ON		ON
Embedded LEDs	1	0	2	1	0	2
Lighting	LED rated 100,000 hours half-life					
Seals	Internal and external gasket panel seal					
Weight	0.09Lb	0.09Lb	0.09Lb	0.09Lb	0.09Lb	0.09Lb