



Maxx® (Model 89076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

Bearings & Bushings

- 5106A Ball bearing, black rubber sealed (15x24x5mm) (2)
- 5107A Ball bearing, black rubber sealed (17x26x5mm) (2)
- 5196A Ball bearing, black rubber sealed (20x32x7mm) (2)
- 5099A Ball bearing, black rubber sealed (6x16x5mm) (2)
- 2728 Ball bearings (5x8x2.5mm) (2)
- 5119A Ball bearings, black rubber sealed (10x15x4mm) (2)
- 5120A Ball bearings, black rubber sealed (12x18x4mm) (2)
- 5180A Ball bearings, black rubber sealed (6x13x5mm) (2)
- 5101 Ball bearings, blue rubber sealed (12x21x5mm) (2)
- 7020 Ball bearings, blue rubber sealed (8x12x3.5mm) (2)

Body & Accessories

- 8915 Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9)
- 8910 Body reinforcement set, Maxx® (fits #8911 body)
- 8913 Body support, rear/ 3x10mm CS (4) (fits #8911 body)
- 8911 Body, Maxx® (clear, untrimmed, requires painting)/ window masks/ decal sheet**
- 8911A Body, Maxx®, blue (painted)/ decal sheet
- 8911T Body, Maxx®, orange (painted)/ decal sheet
- 8911X Body, Maxx®, ProGraphix® (graphics are printed, requires paint & final color application)/ decal sheet**
- 8911R Body, Maxx®, red (painted)/ decal sheet
- 8917 Skid plate, roof (body) (black)/ 3x10mm CS (4)
- 8917X Skid plate, roof (body) (blue)/ 3x12mm CS (4)**
- 8917G Skid plate, roof (body) (green)/ 3x12mm CS (4)**
- 8917T Skid plate, roof (body) (orange)/ 3x12mm CS (4)**
- 8917R Skid plate, roof (body) (red)/ 3x12mm CS (4)**
- 8917A Skid plate, roof (body) (white)/ 3x12mm CS (4)**
- 8912X Tailgate protector, blue/ 3x15mm flat-head screw (4)**
- 8912G Tailgate protector, green/ 3x15mm flat-head screw (4)**
- 8912T Tailgate protector, orange/ 3x15mm flat-head screw (4)**
- 8912R Tailgate protector, red/ 3x15mm flat-head screw (4)**
- 8912A Tailgate protector, white/ 3x15mm flat-head screw (4)**
- 8912 Tailgate protector/ 3x15mm flat-head screw (4)

Bumpers & Skidplates

- 8933 Bumper mount, front
- 8934 Bumper mount, rear
- 8935 Bumper, front
- 8935X Bumper, front (for use with #8990 LED light kit)**
- 8936 Bumper, rear
- 8936X Bumper, rear (for use with #8990 LED light kit)**
- 8945 Skidplate, center
- 8944 Skidplate, front (1), rear (1)

Chassis & Attachments

- 8919 Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads
- 8915 Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x8mm CS (2)/ 3x15mm flat-head machine screw (9)
- 8924 Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x15 CCS (3)
- 8933 Bumper mount, front
- 8934 Bumper mount, rear
- 8935 Bumper, front
- 8936 Bumper, rear
- 8922 Chassis
- 8921 Chassis brace, front
- 8987 Covers, gear (2)
- 8923 Nerf bars, chassis (2)
- 8925 Seal kit, receiver box (includes o-ring, seals, and silicone grease)
- 8938 Shock tower, front (left & right halves)
- 8939 Shock tower, rear (left & right halves)
- 8945 Skidplate, center
- 8944 Skidplate, front (1), rear (1)
- 8976 Wheelie bar
- 8976X Wheelie bar, blue**
- 8976G Wheelie bar, green**
- 8976T Wheelie bar, orange**
- 8976R Wheelie bar, red**
- 8976A Wheelie bar, white**

Cush Drive Components

- 6465 Cush drive key/ pin/ elastomer damper
- 7793X Housing, cush drive (front & rear halves)

- 6447 Spur gear, 46-tooth (1.0 metric pitch)
- 6447X Spur gear, 46-tooth, steel (1.0 metric pitch)**
- 6448 Spur gear, 50-tooth (1.0 metric pitch)
- 6448X Spur gear, 50-tooth, steel (1.0 metric pitch)**
- 6449 Spur gear, 54-tooth (1.0 metric pitch)**
- 6449X Spur gear, 54-tooth, steel (1.0 metric pitch)**

Differential Components

- 8981 Carrier, differential/ x-ring gasket/ o-ring (2)/ 10x19.5x0.5 TW
- 8980 Differential kit, center (complete)**
- 5136X Differential oil kit (1 each: 10K, 30K, 50K weights)**
- 8949 Differential output yoke assembly, front or rear (assembled with external-splined half shaft)
- 8982 Gear set, differential (output gears (2)/ spider gears (4)/ spider gear shaft (2)/ output shaft (2)/ 2.5X13.8 pin (2))
- 8988 Gear, center differential, 44-tooth
- 5041 Grease, premium high performance (20cc)
- 8985 Input gear, transmission, 22-tooth/ 2.5x12mm pin
- 8986 Input shaft, transmission
- 5130 Oil, differential (100K weight) (.7 oz (20cc))**
- 5135 Oil, differential (10K weight)**
- 5040 Oil, differential (20M weight) (standard)
- 5136 Oil, differential (30K weight)
- 8989 Output gear, center differential, hardened steel (2)
- 8978 Ring gear, differential/ pinion gear, differential (front)
- 8977 Ring gear, differential/ pinion gear, differential (rear)
- 8953 Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft)

Driveline Components

- 8952 Carriers, stub axle (left & right)
- 8951 Drive cup (1)/ 4x15.8mm screw pin (use only with #8950X, 8950A driveshaft)**
- 8954 Drive hub, front (1)/ 3x10 screw pin (1)
- 8950 Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
- 8955 Driveshaft, center, aluminum
- 8950A Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup)**
- 8950X Driveshafts, steel constant-velocity (assembled), front or rear (4) (8654, 8654G, or 8654R required for a complete set)**
- 8447A Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)**
- 8447X Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)**
- 8447G Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)**
- 8447R Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)**
- 8447 Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
- 5040 Oil, differential (20M weight) (standard)
- 8953 Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft)**
- 8956 Wheel hubs, hex (2)/ 2.5x12 pins (2)
- 8956X Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)**
- 8654 Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)**
- 8654G Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)**
- 8654R Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)**
- 8957 Wheel washers, black (4)**
- 8957X Wheel washers, blue (4)
- 8957G Wheel washers, green (4)**
- 8957T Wheel washers, orange (4)**
- 8957R Wheel washers, red (4)

Front Suspension & Steering

- 8926 Bulkhead tie bar, front, upper (1)/ lower (2) (steel)
- 8920 Bulkhead, front (upper and lower)
- 8932 Caster blocks (c-hubs), left & right
- 8916 Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)
- 8947 Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
- 8938 Shock tower, front (left & right halves)

Page 2 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89076-4) Parts List

- 8946 Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
- 8937 Steering blocks, left & right
- 8930 Suspension arm, lower, black (left or right, front or rear) (2)
- 8930X Suspension arm, lower, blue (left and right, front or rear) (2)**
- 8930G Suspension arm, lower, green (left and right, front or rear) (2)**
- 8930T Suspension arm, lower, orange (left and right, front or rear) (2)**
- 8930R Suspension arm, lower, red (left and right, front or rear) (2)**
- 8930A Suspension arm, lower, white (left and right, front or rear) (2)**
- 8929 Suspension arms, upper, black (left or right, front or rear) (2)
- 8929X Suspension arms, upper, blue (left or right, front or rear) (2)**
- 8929G Suspension arms, upper, green (left or right, front or rear) (2)**
- 8929T Suspension arms, upper, orange (left or right, front or rear) (2)**
- 8929R Suspension arms, upper, red (left or right, front or rear) (2)**
- 8929A Suspension arms, upper, white (left or right, front or rear) (2)**
- 8941 Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
- 8940 Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)

Hardware

- 3642 Attachment screws, shock (3x12mm shoulder screws) (6)
- 1552 Backplate screws (3x8mm cap-head machine) (6)/washers (6)/wrench
- 2584 Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5, 2.5R, 3.3)
- 8447A Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)**
- 8447X Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)**
- 8447G Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)**
- 8447R Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)**
- 8447 Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
- 5147X Nuts, 5mm flanged nylon locking (steel, serrated) (8)**
- 3236 Screws, 2.5x12mm cap-head machine (6)
- 2577 Screws, 3x10mm button-head machine (hex drive) (6)
- 2587 Screws, 3x10mm cap-head machine (6) (no washer)
- 2551 Screws, 3x10mm countersunk machine (6) (hex drive)
- 4859 Screws, 3x10mm flat-head machine (hex drive) (4)
- 2578 Screws, 3x12mm button-head machine (hex drive) (6)
- 2579 Screws, 3x15mm button-head machine (hex drive) (6)
- 2553 Screws, 3x15mm countersunk machine (6) (hex drive)
- 3646 Screws, 3x15mm flat-head machine (hex drive) (6)
- 2583 Screws, 3x18mm button-head machine (hex drive) (6)
- 2581 Screws, 3x25mm button-head machine (hex drive) (6)
- 2582 Screws, 3x30mm button-head machine (hex drive) (6)
- 2550 Screws, 3x8mm countersunk machine (6) (hex drive)
- 3936 Screws, 4x10mm button-head machine (hex drive) (6)
- 2535 Screws, 4x10mm countersunk machine (hex drive) (6)
- 3937 Screws, 4x12mm button-head machine (hex drive) (6)
- 3938 Screws, 4x14mm button-head machine (hex drive) (6)
- 3933 Screws, 4x16mm button-head machine (hex drive) (6)
- 2589 Screws, 4x20mm button-head machine (hex drive) (6)
- 2596 Screws, 4x25mm button-head machine (hex drive) (6)
- 2595 Screws, 4x35mm button-head machine (hex drive) (6)

Motors & Electronics

- 3463 Cooling fan kit (with shroud), Velineon 540XL motor
- 3475 Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)
- 8987 Covers, gear (2)
- 2092 Gear set (for 2090 servo)
- 3462 Heat sink, Velineon 540XL motor
- 8960 Motor mounts (front and rear)/ pin (1)
- 3461 Motor, Velineon 540XL, 2400Kv 70mm, brushless (assembled with 12-gauge wire and gold-plated bullet connectors) (for Maxx®)
- 3464 Mount, motor cooling fan (fits #3461 motor)
- 2091 Servo case/ gaskets (for 2090 waterproof servo)
- 2090 Servo, digital high-torque (ball bearing), waterproof
- 3465 Velineon® VXL-4s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)

Radio System, Batteries & Chargers

- 2849X 4000mAh 11.1v 3-Cell 25C LiPo Battery**
- 2872X 5000mAh 11.1v 3-Cell 25C LiPo Battery**
- 2888X 5000mAh 14.8v 4-Cell 25C LiPo Battery**
- 2889X 5000mAh 14.8v 4-Cell 25C LiPo Battery**
- 2857X 6400mAh 11.1v 3-Cell 25C LiPo Battery**
- 2878X 8400mAh 11.1v 3-Cell 25C LiPo Battery**
- 2938X Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries to separate balance ports)**
- 1926 Antenna caps, vinyl (2)/ antenna spool

- 1726 Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)**
- 1726A Antenna, tube, black (1)/ vinyl antenna cap (1)/ wire retainer (1)
- 2943 Battery charge indicators (green (4), blue (4), grey (4))**
- 6548 Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)
- 2914 Battery, Power Cell AA Alkaline (4)**
- 2990 Battery/charger complete pack (includes #2972 Dual iD® charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))**
- 2972 Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification**
- 2973 Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto Battery Identification**
- 2971 Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification**
- 2970 Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification**
- 6525 Communication link, telemetry expander**
- 2092 Gear set (for 2090 servo)
- 2968X LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)**
- 2968 LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)**
- 6533 Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
- 6552 Seal kit, expander box (includes o-ring, seals, and silicone grease)**
- 6526 Sensor, auto-detectable, temperature**
- 6527 Sensor, auto-detectable, voltage**
- 6521 Sensor, temperature and voltage (long)**
- 2091 Servo case/ gaskets (for 2090 waterproof servo)
- 2090 Servo, digital high-torque (ball bearing), waterproof
- 6553X Telemetry expander 2.0 and GPS module 2.0, TQi radio system**
- 6550X Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module)**
- 6551X Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander)**
- 6509R TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver)
- 6507R TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)**
- 6528 Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only)
- 6529 Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only)**
- 6530 Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only)**
- 6511 Traxxas Link™ Wireless Module**

Ready-To-Race Model

- 89076-4 Maxx®: 1/10 Scale 4WD Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®

Rear Suspension

- 8927 Bulkhead tie bar, rear, upper (1)/ lower front (1)/ lower rear (1) (steel)
- 8928 Bulkhead, rear (upper and lower)
- 8952 Carriers, stub axle (left & right)
- 8916 Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)
- 8939 Shock tower, rear (left & right halves)
- 8930 Suspension arm, lower, black (left or right, front or rear) (2)
- 8930X Suspension arm, lower, blue (left and right, front or rear) (2)**
- 8930G Suspension arm, lower, green (left and right, front or rear) (2)**
- 8930T Suspension arm, lower, orange (left and right, front or rear) (2)**
- 8930R Suspension arm, lower, red (left and right, front or rear) (2)**
- 8930A Suspension arm, lower, white (left and right, front or rear) (2)**
- 8929 Suspension arms, upper, black (left or right, front or rear) (2)
- 8929X Suspension arms, upper, blue (left or right, front or rear) (2)**
- 8929G Suspension arms, upper, green (left or right, front or rear) (2)**
- 8929T Suspension arms, upper, orange (left or right, front or rear) (2)**
- 8929R Suspension arms, upper, red (left or right, front or rear) (2)**
- 8929A Suspension arms, upper, white (left or right, front or rear) (2)**
- 8941 Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
- 8940 Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)

Shocks (GT-Maxx®)

- 8965X Body, GT-Maxx® shock (aluminum, blue-anodized) (1)
- 8965G Body, GT-Maxx® shock (aluminum, green-anodized) (1)**
- 8965T Body, GT-Maxx® shock (aluminum, orange-anodized) (1)
- 8965R Body, GT-Maxx® shock (aluminum, red-anodized) (1)
- 8962 Rebuild kit, GT-Maxx® shocks (lower cartridge, assembled, pistons, piston nuts, bladders) (renews 2 shocks)

Page 3 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89076-4) Parts List

8964X	Shock caps, aluminum (blue-anodized), GT-Maxx® shocks (4)
8964G	Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4)
8964T	Shock caps, aluminum (orange-anodized), GT-Maxx® shocks (4)
8964R	Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4)
8964	Shock caps, GT-Maxx® shocks/ spring perch/ adjusters/ 2.5x14 CS (2) (for 2 shocks)
8963	Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)
8961	Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o springs) (2)
8961R	Shocks, GT-Maxx®, aluminum (red-anodized) (fully assembled w/o springs) (2)
1667	Silicone shock oil (30 wt), 60cc
8968X	Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968G	Spring retainer (adjuster), green-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968R	Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8966	Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)
8967	Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2)

Spur Gears & Pinion Gears

6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6491X	Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6494X	Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6495X	Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6496X	Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6447	Spur gear, 46-tooth (1.0 metric pitch)
6447X	Spur gear, 46-tooth, steel (1.0 metric pitch)
6448	Spur gear, 50-tooth (1.0 metric pitch)
6448X	Spur gear, 50-tooth, steel (1.0 metric pitch)
6449	Spur gear, 54-tooth (1.0 metric pitch)
6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)

Steering Components

2728	Ball bearings (5x8x2.5mm) (2)
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)
8947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
8946	Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
8948	Toe links, molded composite, 100mm (89mm center to center) (black) (2)

Suspension Linkage

8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)
8948	Toe links, molded composite, 100mm (89mm center to center) (black) (2)

Team Traxxas Items

2514	Decal sheet, racing sponsors
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)
9909	Traxxas® racing banner, red & black (3x7 feet)

Tires & Wheels

8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)
8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)
8972	Tires & wheels, assembled, glued (black wheels, Maxx® All-Terrain tires, foam inserts) (2) (17mm splined) (TSM® rated)
8970	Tires, Maxx® All-Terrain 2.8" (2)/ foam inserts (2)
8956	Wheel hubs, hex (2)/ 2.5x12 pins (2)
8956X	Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)

8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8654R	Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8957	Wheel washers, black (4)
8957X	Wheel washers, blue (4)
8957G	Wheel washers, green (4)
8957T	Wheel washers, orange (4)
8957R	Wheel washers, red (4)
8971	Wheels (black) (2)

Transmission Components

8987	Covers, gear (2)
8985	Input gear, transmission, 22-tooth/ 2.5x12mm pin
8986	Input shaft, transmission
5040	Oil, differential (20M weight) (standard)

Traxxas Tools

3433X	Body reamer (aluminum handle)
3433	Body reamer (plastic handle)
3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
8721	Speed bit handle, medium (one piece)
8720	Speed bit handle, premium, large (rubber overmold)
8722	Speed bit handle, premium, medium (rubber overmold)
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm, 7.00mm, 8.00mm),
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle

Turnbuckles & Threaded Rods

8948	Toe links, molded composite, 100mm (89mm center to center) (black) (2)
------	--

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM