

AF22 - Araflame Coverall

Collection: Araflame Plus

Range: Flame Resistant

Shell Fabric: Araflame Plus: 93% Meta-aramid, 5% Para-aramid, 2% Carbon Fibre 200g

Product information

This winning style has a host of functional features including reflective tape for extra visibility. Triple stitching throughout adds to the strength and durability of AF22. Certified to several EN standards optimal protection is provided for the wearer.

Standards

EN ISO 11612 (A1+A2, B1, C1, F1)

EN ISO 11611 Class 1 (A1+A2)

EN 1149 -5

ASTM F1959/F1959M-12 (ATPV 8.5 CAL/CM² (HAF 70.5%))

IEC 61482-2 IEC 61482-1-1 (Elim 5CAL/CM2)

Araflame Plus

Araflame™ is an inherent flame resistant fabric, made from Aramid fibres. It is extremely flame resistant, lightweight, offers high tensile strength and full anti static protection.

Flame Resistant

This industry leading flame resistant range provides multi standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Features

- CE-CAT III
- Inherent flame resistant qualities will not diminish with washing
- Protection against radiant, convective and contact heat
- Sew on flame resistant industrial wash tape
- Triple-stitched seams for extra durability
- Radio loops for easy clipping of a radio
- Two-way zip for quick and easy access
- Hook and loop cuffs for a secure fit
- Two tier knee pad pockets allowing two positioning options
- 50+ UPF rated fabric to block 98% of UV rays
- 8 pockets for ample storage



AF22 - Araflame Coverall
Commodity Code: 6211331000

Test House

Aitex (Notified Body No.: NB: 0161)
 Plaza Emilio Sala 1
 , ESPAGNE
 Cert No: 20_2209_00_0161

Wash Care



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
AF22ORRS	Orange	65.0	40.0	36.0	1.0250	0.0936	5036108188802	15036108675798
AF22ORRM	Orange	65.0	40.0	36.0	1.0000	0.0936	5036108188796	15036108675781
AF22ORRL	Orange	65.0	40.0	36.0	0.9600	0.0936	5036108188789	15036108675774
AF22ORRXL	Orange	65.0	40.0	36.0	1.0700	0.0936	5036108188819	15036108675804
AF22ORRXXL	Orange	65.0	40.0	36.0	1.0400	0.0936	5036108188826	15036108675811
AF22ORRXXXL	Orange	65.0	40.0	36.0	1.0600	0.0936	5036108188833	15036108675828