

ATV SXS POWER 4T 10W-50

High performance lubricant for ATV, SxS & SSV

100% Synthetic - Ester

TYPE OF USE

ATV - All Terrain Vehicle, SxS - Side by Side, SSV - Side by Side Vehicle, and buggy fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2, 3, 4 or 5 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...

Recommended for ATV, SxS, SSV and buggy used for leisure and recreation.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCE

STANDARDS API SN / SM / SL / SJ

SPECIFICATIONS JASO MA2 under N° M033MOT174

100% Synthetic – Ester lubricant for improved oil film resistance at high temperatures.

Formula reinforced with Ester and anti-wear additives for improved oil film shear resistance and for increased gear protection and life time duration.

The JASO MA2 approval guarantees the efficient high friction level to secure the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

Optimized Phosphorus and Sulfur contents for better operating conditions of catalytic converters required to meet latest emission regulation.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use. Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Color	Visual	Red
Viscosity grade	SAE J 300	10W-50
Density at 20°C (68°F)	ASTM D1298	0.861
Viscosity at 40°C (104°F)	ASTM D445	120.4 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	18.2 mm ² /s
Viscosity index	ASTM D2270	168
Pour point	ASTM D97	-33°C / -27°F
Flash point	ASTM D92	232°C / 450°F
TBN	ASTM D2896	8.3 mg KOH/g