



BOSCH LSU4.9 Wideband Oxygen Sensor

SKU(s): 710FU0015

INCLUDED PARTS

(1) BOSCH O2 Sensor

(2) Crush Washer

REQUIRED TOOLS

22mm Open End Wrench



Installation Steps:

Step 1: Unplug the six-pin connector from the car.

Step 2: Loosen the O2 sensor out of the exhaust with a 22mm open end wrench.

Step 3: Install the new BOSCH O2 sensor into the exhaust. Anti-seize is already on the new threads. Tighten down with 22mm wrench.

Step 4: Reconnect the six-pin connector back into the car.

Thank you for choosing Evolution Powersports products. If you require further assistance, please call our Tech Support @ (715) 247-3862

***Note:** This product is exempt from the emission standards and related requirements of 40 C.F.R. § 1051 as provided by 40 C.F.R. § 1051.620, and California law [e.g., vehicle code §§ 27156 and 38391]. This product is sold only for use in connection with EPA certified, purpose-built, nonroad vehicles used solely for closed course, nonroad competition/racing and not used for any recreational purpose or on public highways or right of ways maintained by and open to the public. This product is sold only in connection with machines that do not fall under state and/or federal noise or emission standards/regulations. Purchasers who/that purchase this product represent and warrant that the product is purchased only in connection with EPA -certified, emission-regulations-exempt and noise-regulations-exempt competition/racing vehicles as interpreted under applicable state and/or federal law. Questions: Call Evolution Powersports at (715) 247-3862.*