



X3 EVP Quick Belt Changing Tool Kit

SKU(s): 875FU0013

INCLUDED PARTS

(1) Threaded Handle for
Secondary

(1) Helix Cover





INSTALLATION INSTRUCTIONS

Step 1: The EVP Quick Belt Changing Tool works with both OEM and Shift-Tek helixes.

Step 2: Place the helix cover over the threads of the tool, with the handle at 90-degrees thread the tool into the helix. Make sure the ball bearings are facing the helix cover.



Step 3: Once threaded in, pull the handle 90-degrees till it locks into position. Doing this will compress the helix into the secondary, moving the sheaves apart, allowing the belt to be removed within seconds.



WE'D LOVE TO HEAR FROM YOU - LEAVE A REVIEW & STAY CONNECTED!   



Step 4: Replace the belt, release the belt changing tool and spin the tool out of the helix. Spin the secondary 10 times allowing the drive belt to seat properly in the secondary.

Thank you for choosing Evolution Powersports products. If you require further assistance, please call our Tech Support @ (715) 247-3862

***Note:** This product is exempt from the emission standards and related requirements of 40 C.F.R. § 1051 as provided by 40 C.F.R. § 1051.620, and California law [e.g., vehicle code §§ 27156 and 38391]. This product is sold only for use in connection with EPA certified, purpose-built, nonroad vehicles used solely for closed course, nonroad competition/racing and not used for any recreational purpose or on public highways or right of ways maintained by and open to the public. This product is sold only in connection with machines that do not fall under state and/or federal noise or emission standards/regulations. Purchasers who/that purchase this product represent and warrant that the product is purchased only in connection with EPA -certified, emission-regulations-exempt and noise-regulations-exempt competition/racing vehicles as interpreted under applicable state and/or federal law. Questions: Call Evolution Powersports at (715) 247-3862.*