



X3 High Flow Air Filtration Media With Prefilter

SKU(s): 203FP0001

NOTE: Never oil the filter as this will only degrade its performance.

Absolute Efficiency

SuperNano-Web Air Filters are some of the most efficient filters on the market. Our filters remove more dust than a filter manufactured using traditional cellulose filter media. Our proprietary base media is manufactured from time honored cellulose, along with synthetic polyester. This base blend allows for a high flowing media with excellent dust holding capabilities. Once we add our SuperNano-Web layer over our base media, the SuperNano-Web beings to act very much like a spiderweb by attracting dirt like a magnet to the surface of our media. The result is clean, fresh air for your engine.

Better Air Flow

SuperNano-Web Air Filters allow more airflow than typical filters that use cellulose media alone. Cellulose fibers are larger than nanofibers and have larger spaces between the fibers, which causes contaminants to load in the depth of the media and plug the airflow path, which in results suffocating the air flow to your motor. The synthetic nanofibers in the SuperNano-Web Filter media have submicron diameters and small inter-fiber spaces, which result in more contaminants being captured on the surface of the media. This surface loading technique allows the SuperNano-Web to stop the smaller particles. This equates to a high flowing media with excellent dirt stopping ability.

Cleanable - Longer Life

When cleaning according to specifications and used in normal service, SuperNano-Web Air Filters will perform well past the service life of a typical vehicle. SuperNano-Web Air Filters remain active for up to 2000 miles (Off Road Vehicles) and/or one year before requiring cleaning; depending on driving conditions. The more the filter is cleaned, the better the engine will perform.

Cleaning

SuperNano-Web Air Filters should be cleaned every year or every 2000 miles, whichever comes first – more if operated in a race or dusty conditions. Carefully remove the filter from the housing. Clean the housing with a shop towel, being careful not to knock foreign debris into the air inlet. Using low pressure compressed air (50-70 PSI) direct the air from the inside of the filter towards the outside. This will blow debris from the outside surface off and restore your air filter to optimum condition. **NOTE:** Never blow air from the outside of the filter, inward. Discoloration and staining will occur over time. This will NOT impact filter restriction or efficiency.



INSTALLATION INSTRUCTIONS

Thank you for choosing Evolution Powersports products. If you require further assistance, please call our Tech Support @ (715) 247-3862

Note: This product is exempt from the emission standards and related requirements of 40 C.F.R. § 1051 as provided by 40 C.F.R. § 1051.620, and California law [e.g., vehicle code §§ 27156 and 38391]. This product is sold only for use in connection with EPA certified, purpose-built, nonroad vehicles used solely for closed course, nonroad competition/racing and not used for any recreational purpose or on public highways or right of ways maintained by and open to the public. This product is sold only in connection with machines that do not fall under state and/or federal noise or emission standards/regulations. Purchasers who/that purchase this product represent and warrant that the product is purchased only in connection with EPA -certified, emission-regulations-exempt and noise-regulations-exempt competition/racing vehicles as interpreted under applicable state and/or federal law. Questions: Call Evolution Powersports at (715) 247-3862.

WE'D LOVE TO HEAR FROM YOU - LEAVE A REVIEW & STAY CONNECTED!   