



## ROOF PROTECTION MATS

Specially designed to provide sound proofing and shock absorption under heavy industrial equipment such as generators and provide the perfect protection for felt roofs.

### Specifications

Dimensions	2mx1m
Thickness	18mm ± 2mm
Weight	36kg
Colours	Black, Brown, Red, Grey, Green
Finish	Flat Top, Brick
Units per Pallet	50
Area coverage	2m <sup>2</sup>
Density	900kgm <sup>3</sup>

### Technical Test Data

Critical Fall Height – BS EN 1177	0.8m ± 0.1m
Slip Resistance – BS EN 13036	Wet 60µ Dry 81µ
Hot Metal Nut Test – BS 4790:1987	Time of smoking (after flame reached an extinct status) 15s Low radius of effect of ignition
Flammability Test - EN ISO 11925-2	Exposure time and Mode: 15s and application to the edge. Flame tip did not reach or pass 15mm. No burning droplets were observed.
EN 13501-1	TBA

### Winds Lift Testing

Mat	Flat	Leading edge raised 25mm	Leading edge raised 50mm	Bonded to surface
18mm ± 2mm Brick (bevelled edge into wind)	86.5 mph > Force 12 hurricane	45.7 mph Force 8 gale	46.6 mph Force 7 near gale	

BLACK 0% SRI, GREY 31% SRI, WHITE 100% SRI

\*The SRI of the mat can be improved by adding a pigment/colour.

Perfect For Roofs & Under Heavy Machinery

We Can Ship This Product To You Worldwide

Designed To Provide Sound Proofing & Shock Absorption

100% Irish Made

## NR RUBBER PRODUCTS

Model Cottage, Chapel Road, Dromiskin, Co Louth, Ireland

[www.nrrubberproducts.com](http://www.nrrubberproducts.com)

Phone:

+353 (0) 87 937 3497

+353 (0) 42 938 2900

Email:

[info@nrrubberproducts.com](mailto:info@nrrubberproducts.com)