



FUEL CONTAINMENT DOOR

Installation Instructions JEEP WRANGLER JK

QTY	Parts List
1	Fuel Door Cover
1	Installation Instructions

Difficulty Level: Easy

Product Support

1-888-531-7183

info@combat4x4.com

Tool List
#4 Phillips Screwdriver
#2 Flat Head Screwdriver



WARNING:
YOU ARE WORKING ON THE FUEL SYSTEM!
TAKE PRECAUTIONS TO KEEP AWAY ANY SOURCE OF HEAT OR FLAMES.

Notes and Maintenance

- Before you begin installation, read all instructions thoroughly.
- Proper tools will improve the quality of installation and reduce the time required.
- For black finishes, mild soap may be used to clean the product.
- Periodic inspections should be performed to ensure all mounting hardware remains tight.
- Mild automotive detergent may be used to clean the product. Do not use dish detergent, abrasive cleaners, abrasive pads, wire brushes or other similar products that may damage the finish.

Feedback

COMBAT OFF ROAD industry leading warranty. Register your purchase by visiting: www.combat4x4.com/registration

Be social, tag us on your install or out on the trail enjoying, use: #combat4x4 and #combatoffroad



FUEL CONTAINMENT DOOR

Installation Instructions JEEP WRANGLER JK

Step 1

Locate the phillips head screws holding the tail light in place.

NOTE: ONLY REMOVE THE TWO INNER SCREWS.



Step 2

Pull the tail light out of the body on the side where you removed the screws and then slide it towards the center of the vehicle.



Step 3

Secure the light or unplug it from the wiring harness.





FUEL CONTAINMENT DOOR

Installation Instructions JEEP WRANGLER JK

Step 4

Loosen and remove the fuel cap



Step 5

Remove fuel cap retaining line using
#2 flat head screwdriver



Step 6

Locate the tabs on the back of the filler
neck housing. Depress the top tabs first to
allow release from the body.





Step 7

After depressing the tabs, pull the housing away from the body starting at the top and working your way around.

NOTE: MAKE SURE ALL THE TABS PASS THROUGH THE BODY



Step 8

Pull the housing away from the filler neck. The seal around the filler necks is required to be reused with the new cover.



Step 9

Reinstall the seal on the new fuel door.

NOTE: ORIENTATION IS THE SAME AS THE OEM UNIT





Step 10

NOTE: TAB (SOME UNITS)

As required this may need removal depending on fit up with your vehicle.



Step 11

As required, remove tab using side cutter or sharp blade. Depending on body alignment with unit.



Step 12

Press the new fuel door over the filler neck and clip into body of vehicle.





FUEL CONTAINMENT DOOR

Installation Instructions JEEP WRANGLER JK

Step 13

Reinstall the fuel cap and retaining line, close the fuel door cover.



Step 14

Reinstall the tail light using the original hardware.

NOTE: DO NOT OVER TORQUE THE SCREWS AS TAIL LIGHT CRACKING COULD OCCUR



! **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov