



SCT 5-40 M

Dry wall screw gun with collated screw magazine up to 5 mm

Autofeed screwdriver for quick repeated screw fittings with quiet clutch.

Product number: 7 213 06 50 01 8

Details

- > Drywall construction screwdriver SCT 5-40 X incl. magazine M55 X.
- > QuickIN for tool-free removal collated strips, setting of screw length and driving depth as well as quick cleaning.
- > Speed-optimised; for rapid fixing of plasterboard to wood or metal frames.
- > One of the lightest screwdrivers in its class.
- > Silent FEIN CLIC-STOP clutch.
- > Point placement accuracy with infinitely variable electronic speed setting.
- > Patented screw transport system.
- > Additional depth stop for non-collated screws.
- > Ideally suited for single-hand use.
- > Magazine can be rotated through 360 degrees.
- > Robust shell casing.
- > Market-leading ergonomics with FEIN Sensitive handle.
- > FEIN high-power motor.
- > Vibration-free stop.
- > Practical hand strap.

Price includes

- ✓ 1 Collated cartridge for collated screws
- ✓ 1 depth stop
- ✓ 1 bit ¼" for cross-slotted screws size 2 / Phillips (form H) with dust-protection ring
- ✓ 1 belt clip
- ✓ 1 bit ¼" size 2 / Phillips (form H), long
- ✓ 1 magnetic holder for bits ¼"
- ✓ 1 hand strap
- ✓ 1 plastic carrying case

Technical data

TECHNICAL DATA

Input	450 W
Output	250 W
Speed, full load	0 - 2,700 rpm
Speed, no load	0 - 4,000 rpm
tec_max._drehmoment_(har	12 / - Nm
tec_schrauben_d_global	5 mm
tec_schraubenlange_global	25 - 55 mm
Rapid change chuck	1/4 in
tec_kabel_mit_stecker_globa	5 m
tec_gewicht_epta_global	1.60 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	81 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	92 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	98 dB 3 dB
Vibration value 1 α_{hv} 3- way Uncertainty of measured value K α	0,8 m/s ² 1,5 m/s ²

Application examples

