



PACKAGING
FLOTATION
HOME & COMMERCIAL INSULATION
DOCK ACCESSORIES

Home Office P.O. Box 148 - Gravette, AR 72736
(479)787-5991 - Fax (479)787-6410 - Wats 800-489-5991

WARNING

Please remember the flotation/lift devices you are handling are made of Polyethylene, which is a plastic, and as in any plastics if dropped or handled inappropriately in cold weather there is a chance of breakage, please handle these products with the appropriate care, and do not drop. Any breakage resulting due to improper handling will NOT be covered under the warranty agreement.

Insul-Bead Corporation Limited Warranty

Insul-Bead Corporation (Seller) warrants it's flotation device solely to the original purchaser against cracking, peeling, sloughing, and deterioration from ultraviolet rays while retaining its resiliency under normal usage and service for a period of 10 years from proven date of purchase and that it will be free of defects in workmanship, when properly installed and maintained, under normal use and service.

Purchaser's remedy hereunder in any case is expressly limited to repair or replacement of the defective flotation device, or at seller's election, to the repayment of or crediting purchaser with an amount not to exceed original purchase price, only with an original invoice of purchase. In the event Seller elects to refund the purchase price, the refund shall be prorated reflecting a deduction for period between original purchase date and the notice of claim under the warranty. Purchaser shall provide seller with an opportunity to inspect and test any flotation device claimed to be defective. All products will be returned to seller for warranty evaluation.

In no event shall seller be liable for any defective flotation device if examination reveals that the defective condition is attributed to negligence, misuse, alteration, accident, improper installation, or maintenance, improper repair, or Act of God

Seller makes no representation or warranty of any other kind, express or implied with respect to the product(s) sold hereunder as to merchantability, fitness of purpose, or legality of use in any jurisdiction. Seller shall not be liable for any loss of use, costs or fees or any liability for direct, indirect or consequential damages or delays. Seller shall not be liable for any labor costs involved. No other person, firm or corporation can bind seller to any warranty other than herein above stated.

Any float determined by Insul-Bead Corporation to be replaced is covered by its limited warranty ,as described above, for the following time period from purchase date by original owner: 100% non-prorated for 10 years; 50% in 11th year; 40% in 12th year, 30% in 13th year, 20% in 14th year, 10% in 15th year of current.

New 15-year warranty effective on purchases after November 01, 2007. Drums purchased prior to November 01, 2007 are covered under the previous 10-year warranty.

The terms and conditions of this warranty will abide by the laws of the State of Arkansas



**PACKAGING
FLOTATION
HOME & COMMERCIAL INSULATION
DOCK ACCESSORIES**

**Home Office P.O. Box 148 - Gravette, AR 72736
(479)787-5991 - Fax (479)787-6410 - Wats 800-489-5991**

RECOMMENDED PROCEDURE FOR USING INSUL-BEAD FLOAT DRUMS

STORAGE:

- Store float drum upside down with plug hole facing down.
- Do not store float drum with vent plug inserted in areas of direct sunlight or hot temperatures.
- Dropping float drum may result in damages, especially in cold weather.
- Do not stack over ten feet high.

VENT PLUG INSERTING: (When Applies)

- Do not insert vent plug until you are ready to use float drum.
- Before inserting vent plug, make sure to drain the float drum of any water that might have seeped through the plug hole.
- Apply silicone or pipe sealer on vent plug to keep the inside of the float drum waterproof.
- Use a 5/16" Allen wrench to insert vent plug.
- Thread vent plug in float drum until the top of the plug is level with the top of the float drum.
- There is a new style of venting caps that don't require you to install anything. Call mfg. if you need more information.

FRAME SUPPORT:

- Both sides and ends of float drum must be supported by the dock frame.
- Minimum frame support of float drum must be every 48" x 48" or every sixteen square feet.

ATTACHEMENT:

- All mounting slots of float drum must be bolted or lagged to the frame if dock is exposed to wave action; otherwise, at least four mounting slots must be used to mount float drum.
- Minimum of 5/16" bolts or lag screws required.

INSTALLATION & REMOVAL OF DOCK:

- When installing or removing dock, lift the dock sections-do not slide. Sliding float drums may result in puncturing or wearing a hole in the walls of the float drum.
- In areas where severe ice movement occurs, dock must be removed during winter months.

NOTES: Warranty applies only for the sole purpose of flotation of docks.
Other uses may not apply.