



## Weatherite – Data Sheet

### Description:

**Weatherite** is a self-priming water based acrylic paint formulated on a premium 100% acrylic resin to impart a tough flexible finish and to maximise performance in all exterior conditions. When dry **Weatherite** has excellent abrasion resistance and is fully washable.

### Physical Properties

<b>Resin Type:</b>	Pure Acrylic
<b>Solvent:</b>	Water
<b>Colour:</b>	White, and full range of tinted colours
<b>Finish:</b>	Low Sheen, Semi-Gloss, Gloss
<b>Drying time:</b>	1 hour @ 18°C
<b>Recoat time:</b>	2 hours @ 18°
<b>Dry Film Thickness:</b>	75µ minimum
<b>No. of coats:</b>	3
<b>Theoretical Coverage:</b>	12m <sup>2</sup> /litre per coat to attain 75m <sup>2</sup> .
<b>Primer Needed:</b>	Recommended for most substrates
<b>Thinning &amp; Cleaning:</b>	Thin as required, cleanup with water

### Performance:

- Excellent adhesion to natural timber, masonry, old paint work and most primers.
- Maybe used as a roof coating.
- Easy to clean and maintain
- Can be used for potable water.
- Flexible - Resists cracking & peeling for long-term weather protection
- Self-Priming - No primer required on most exterior surfaces for faster painting
- 100% Acrylic - Resists chalking and fading in the extremes of sun and weather
- Inhibits growth of mould & mildew - powerful formula to protect the surface
- Made and developed in New Zealand for lasting protection in all New Zealand conditions

### Limitations:

- Do not apply when temperature is below or expected to fall under 10°C.
- Use **All Prime** on all surfaces that are deteriorating.
- Disconnect downpipes if painting areas that are used for potable water. Reconnect after 1<sup>st</sup> rainfall.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Paint Tech makes no representation as to the completeness and accuracy thereof. In no event will Paint Tech be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.

**Substrate Preparation:**

Ensure all surfaces are clean, dry and dust free. If mould and fungus are present use **Paint Tech Moss and Mould Kill**. Water blasting is the recommended method of surface preparation.

**NB:** Although **Weatherite** has excellent adhesion to most substrates it is recommended that a suitable primer be used at all times.

**Application:**

**Weatherite** may be applied by brush, roller, speed brush or spray. Thinning with water is only recommended for spray application.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Paint Tech makes no representation as to the completeness and accuracy thereof. In no event will Paint Tech be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.