Safety Data Sheet:

SECTION 1: Identification of the Material and Supplier

Emergency Phone:	New Zealand Poisons Centre 0800 764 766	
Phone:	09 483 4833	
Product Name: Recommended Use: Company Name:	Lightning Paint Stripper Methylene chloride based paint stripper Commercial Coatings Manufacturers Ltd Address:	P.O. Box 33 529, Takapuna, Auckland 0622.

Hazards Identification Section 2:

Hazard Classification: Classified as Dangerous Good under NZS 5433:2007

Substance Classification: 6.1D, 6.3A, 8.3A, 6.6B, 6.7B, 6.8B, 6.9B, 9.3C

Hazard Statements: Causes skin irritation Harmful to aquatic life Keep out of reach of children and pets. Do NOT induce vomiting if swallowed.

Section 3: **Composition/Information on Ingredients**

Ingredients: Methylene Chloride Ammonia 910 Other ingredients

% 90% - 96% 0.5% + / - .14% - 10%

CAS No 75-09-2 7664-41-7 Proprietary

Section 4: **First Aid Measures**

Eyes: Severely irritating to eyes Swallowed: Do not induce vomiting. Give glass of water and call NZ Poisons Centre Removes oils and dries skin. Wash contaminated area with warm water an Skin: Inhaled: Remove to fresh air and allow to recover. If patient is uncomfortable call doctor. **Chronic Health Affects:** None Identified

Advice to Doctors: **Treat Symptomatically**

Section 5: **Fire Fighting Measures**

Extinguisher:	Foam, Carbon Dioxide, Dry Chemical
Hazards from Burning:	Will emit toxic fumes on burning. Phosgene, Hydrogen chloride and
	carbon monoxide
Precautions for firefighters: Flash Point:	Keep containers cool. Wear breathing apparatus and protective clothing. >90°C will not support combustion.

Section 6: Accidental Release Measures

Emergency Procedures:	Keep onlookers away and avoid breathing vapours or dust. Prevent spills from entering sewers or waterways.
Minor Spills:	Clean up immediately. Use absorbent clean materials such as sawdust Keep spills and cleaning runoffs out of sewers and waterways Wear protective clothing and breathing equipment Sweep up Store in separate container for recovery/disposal
Major Spills:	Contain spill with inert materials such as sand Keep spills out of sewers and waterways Restrict access to area Notify Fire Brigade Wear protective clothing and breathing equipment Stop leak if safe to do so. Collect recoverable material into labeled containers and dispose in accordance with local by-laws and regulations.

Section 7: Handling & Storage

Precautions for Safe Handling:	Keep out of reach of children. Avoid skin and eye contact. Avoid all Potential sources of ignition.
Storage temperatures:	1°C - 40°C Avoid damaging containers. Keep lids on securely when not in use. Do not store with food products.

Section 8 Exposure Control / Personal Protection

Occupational Exposure Limit:	No value assigned for	or this product but individual raw materials are:
	Methylene chloride	50ppm (174mg/m ³)
	ive Cover-All's. PVC or	ses when applying any paint rubber gloves and approved safety boots.

Section 9: Physical & Chemical Properties

Appearance:	Clear hazy viscous liquid
Odour:	Sweet solvent smell
Vapour Pressure:	N/A
Vapour Density (air = 1):	>1
Solubility in water:	miscible.
Boiling Point:	42°C

Section 10: Stability & Activity

Chemical Stability: Conditions to avoid:	Stable under normal handling and storage conditions Avoid contact with foodstuffs, contact with heat and ignition sources. Avoid contact with strong oxidizing agents.
Hazardous Decomposition:	Only on burning are toxic fumes given off. See Fire Fighting measures.
Products:	phosgene, Hydrogen chloride, Oxides of carbon
Hazardous Reactions:	Not subject to hazardous polymerization.

Section 11: Toxicological Information

Ingestion:	Harmful if swallowed. Will burn and cause pain to throat, trachea, respiratory tract and gastrointestinal tract.
Eye Contact:	Severe irritant to eye membranes, get medical attention after cleaning with water.
Skin Contact:	The product will cause pain and burns to the skin. May have anesthetic effect This product when in contact with skin can increase in severity over time causing blisters and burns. It is important to wash skin contamination off immediately and thoroughly.
Inhalation:	Vapours may be harmful and may cause discomfort and be irritating to the upper respiratory tract. Possible symptoms are light headedness, nausea and possible unconsciousness at high concentrations.
Chronic affects:	The product contains methylene chloride a substance suspected of causing cancer and may cause damage to organs through prolonged and repeated exposure by oral, dermal or inhalation exposure routes. Adverse effects may occur to blood, hematopoietic system and kidneys. Toxological information: Oral LD50 Rat; 1410mg/kg.

Section 12 Ecological Information

Ecotoxicity: Avoid contaminating waterways.

Section 13: Disposal Considerations

Disposal methods: For large quantities consult a licensed waste contractor. For small quantities: do not pour leftover paint down drains. Leftover paint can be disposed of by brushing on to cardboard and allowing to dry. The dried material can then be disposed of in landfill. Check for recycling of containers in a recycling programme.

Section 14: Transport Information

UN Number:	UN1593
Dangerous Goods Class:	6.1 Toxic and Infectious Substances - Toxic Substances
Hazchem Code:	2Z
Packaging Group:	III
Shipping Name:	DICHLOROMETHANE
EPG	37 Toxic And/Or Corrosive Substances Non-Combustible

Section 15: Regulatory Information

Group Standard:	HSR002531; Cleaning products Toxic (6.7) Group Standard 2006. Refer <u>www.ermanz.govt.nz</u> for information on controls.
Approved Handler:	Not Required for general use.

Section 16: Other Information

Date of Preparation: References: 6th August 2014 SDS's for raw materials

Abbreviations:

CAS No TWA Chemical Abstract Service number Time weighted average

Version 1: 4 Pages - 06/08/2018