# **µLC Test System**

www.bosch-motorsport.com





- ▶ User-friendly interface
- ► Customer defined features feasible
- ▶ Prepared for test automation
- ► Favorable test setup, consuming low space
- Simulation of typical automotive interfaces combined in one unit

The new and modern hardware-in-the-loop test system  $\mu$ LC Test System is suitable for mobile application, measuring a compact 17 cm x 11 cm x 6 cm. Initial test setup typically takes under ten minutes, since the system allows for a simple test setup.

It is a compact open-loop test system for quality assurance of control unit development and combines the simulation of all typical automotive sensors and communication protocols in one unit. Its interface is userfriendly and enables an easy operation and evaluation. The  $\mu$ LC Test System is especially used for automotive control units with typical interfaces for sensors and bus systems such as analogue/digital inputs and outputs, PWM signals, SENT, CAN, LIN and speed sensors.

#### **Functions**

### **Engine Speed Simulation**

- Up to 20,000 rpm
- Supported sensors: Hall, inductive, DG23i, TL4953
- Up to 2 crankshafts, up to 4 camshafts
  - each is independently configurable
  - auxiliary shaft
  - -180 to 180° camshaft adjustment
- · Oscilloscope trigger signal for easier monitoring
- Error simulation for engine position management EPM

# **Vehicle Busses**

- 2 \* CAN, up to 1 MBit/s switchable 120 Ohm CAN bus terminator
- · LIN Master/Slave

• SENT, full J2716 Jan. 2012 standard 4 Outputs, alternative to PWM output

### **Digital Interfaces**

- 6 \* Digital Out, max. 200 mA in total Output modes: Ground, 12 V, High impedance
- 2 \* Relays, max. 10 A, separate ECU power supply possible and incl. main relay sensing
- 2 \* PWM input, 1 Hz to 20 kHz
- 4 \* PWM output, max. 90 mA in total, 0.1 Hz to 20 kHz Output voltages: 12 V, 5 V, GND
- Complex PWM with sub signals, each separately adjustable in frequency, duty cycle and pulse count


#### **Analogue Interfaces**

- 8 \* 10 bit DAC 0 to 5 V, max. 5 mA Internal or external supply
- 4 \* 12 bit DAC 0 to 5 V, max. 5 mA
- 6 \* 12 bit ADC 0 to 40 V, GND reference

# **Additional Features**

- · Cylinder pressure simulation
  - Up to 8 cylinders with one device
  - Expandable with multiple devices
- · USB connection completely galvanic decoupled
- All in- and outputs short-circuit protected and ESD protected
- EMC tested
- · Expansion boards for additional HW features
- Multi device support with sync option for engine speed signals

# **Test Setup**



Note: Calculation intensive modules like cylinder pressure simulation can cause a limitation of e.g. the max. engine speed.

Technical Specifications	
Operating voltage	12 V DC
Current consumption	typ. < 1 A
ECU voltage	12 V / 24 V DC
ECU current	10 A
Permissible operation temperature	0°C to 40°C
Housing material	Aluminum
Dimensions	175 mm x 107 mm x 61 mm
Weight	690 g



The screenshot shows the MicroLC Software with analog outputs, crank-/ camshaft, RPM and complex PWM.

# **Ordering Information**

## μLC Test System

Order number F 02U V02 303-02

#### Represented by:

Europe: Bosch Engineering GmbH Motorsport Robert-Bosch-Allee 1 74232 Abstatt Germany Tel.: +49 7062 911 9101 Fax: +49 7062 911 79104 motorsport@bosch.com www.bosch-motorsport.de North America: Bosch Engineering North America Motorsport 38000 Hills Tech Drive Farmington Hills, MI 48331-3417 United States of America Tel.: +1 248 876 2977 Fax: +1 248 876 7373 motorsport@bosch.com www.bosch-motorsport.com Latin America:
Robert Bosch Ltda
Motorsport
Av Juscelino Kubitscheck de
Oliweira 11800
Zip code 81460-900
Curitiba - Parana
Brasilia
Tel.: +55 41 3341 2057
Fax: +55 41 3341 2779

Asia-Pacific:
Bosch Engineering Japan K.K.
Motorsport
18F Queen's Tower C, 2-3-5 Minato Mirai
Nishi-ku, Yokohama-shi
Kanagawa 220-6218
Japan
Tel.: +81 45 650 5610
Fax: +81 45 650 5611
www.bosch-motorsport.jp

Australia, New Zealand and South Africa:
Robert Bosch Pty. Ltd
Motorsport
1555 Centre Road
Clayton, Victoria, 3168
Australia
Tel.: +61 (3) 9541 3901
motor.sport@au.bosch.com