

SAFETY DATA SHEET

Section 1 - Product and Company Identification

Product Name: 5365 JOLIE PAINT SLATE Product Code: 5365

Trade Name: 5365 JOLIE PAINT SLATE

Company Identification:

Davis Paint Company

1311 Iron Street

P.O. Box 7589

N. Kansas City, MO 64116

Contact Information :

Emergency Phone : (816)-471-4447

Information Phone : (816)-471-4447

Name of Preparer : Env., Health, & Safety Dept.

For emergencies involving a spill, leak, fire, exposure,
or accident - Contact INFOTRAC phone: (800)-535-5053

Product Use: PAINT - General Purpose Use.

Not recommended for: No data available.

Section 2 - Hazards Identification

GHS Ratings:

Carcinogen

1A

Known Human Carcinogen Based on human evidence

GHS Hazards

H350

May cause cancer

GHS Precautions

P201

Obtain special instructions before use

P202

Do not handle until all safety precautions have been read and understood

P281

Use personal protective equipment as required

P308+P313

IF exposed or concerned: Get medical advice/attention

P405

Store locked up

P501

Dispose of contents/container that comply with local, State, Federal, or
International regulations as applicable.

Signal Word: Danger



Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Limestone	1317-65-3	20.00% - 30.00%
Talc	14807-96-6	5.00% - 10.00%
Nepheline syenite	37244-96-5	1.00% - 5.00%
Titanium dioxide	13463-67-7	4.00%
Quartz	14808-60-7	0.30%

Section 4 - First Aid Measures

Inhalation:

Remove to fresh air. Vapor or mist can cause headache, nausea, and irritation of the nose, throat and lungs, in a poorly ventilated area. If symptoms persist, seek medical attention.

Eye contact:

Direct contact may cause irritation. Remove contact lenses if necessary, and flush with plenty of clean water while holding eyelids open. Do not rub eyes. Get medical attention if irritation or symptoms persist.

Skin contact:

Irritating to the skin on repeated or prolonged contact. Wash with plenty of soap and water. If irritation persists or a rash develops, seek medical attention.

Ingestion:

Can cause gastrointestinal irritation. If swallowed, wash mouth out with water. Do not induce vomiting unless directed by medical personnel. If large amounts are swallowed, give one or two glasses of water and seek medical attention.

Notes to Physician:

Treat symptomatically. Contact Poison Control Center if large quantities have been inhaled or ingested.

Section - 5 Fire Fighting Measures

Flash Point: 100 C (212 F)

LEL:

UEL:

Extinguishing media:

Foam, CO2, Dry Chemical.

Unusual Fire and Explosion Hazards:

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product generally will not burn but may spatter if temperature exceeds the boiling point of product.

Hazardous Combustion Products:

Carbon monoxide, carbon dioxide, aldehydes, hydrocarbons, and other products of incomplete combustion.

Firefighting Procedure:

Firefighters should wear self contained breathing apparatus if material is involved in a general fire.

Section 6 - Accidental Release Measures

Spill Leak / Procedures:

Dike spill area. Ensure adequate ventilation. Wear appropriate personal protective equipment.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See section #12 for further Ecological information.

Methods and Materials for Containment and Cleaning Up:

Contain spillage. Then collect with inert absorbent materials. Dispose of in accordance with applicable regulations.

Section 7 - Handling and Storage

Handling Precautions:

Do not use until all safety precautions have been read and understood. Use personal protection found in section 8. Smoking, eating, or drinking should be prohibited in the application area.

Storage Requirements:

Keep containers closed and upright when not in use. Store in cool well ventilated areas away from heat and direct sunlight. Previously opened containers, carefully reseal. KEEP FROM FREEZING! Wash thoroughly after handling.

Section 8 - Exposure Control and Personal Protection

Engineering Controls:

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits.

Provide readily accessible eye wash station.

Use of protective creams, head caps etc, is recommended.

Personal Protective Equipment**Respiratory Protection:**

Do not breathe vapors or mist. Wear an appropriate, properly fitted respirator (NIOSH approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits.

Skin and Body Protection:

Use polyethylene gloves to avoid contact with product. Gloves must be impervious to soap and water. Wear suitable protective clothing.

Eye Protection:

Use safety eyewear with splash guards or side shields, or goggles.

Section 9 - Physical and Chemical Properties

<p>Explosive Limits: N/A</p> <p>Autoignition temperature: N/A</p> <p>Physical State Liquid</p> <p>COATING VOC #/G 0.000</p> <p>Vapor Pressure: 13.1 mmHg</p> <p>Vapor Density Heavier than air.</p> <p>Specific Gravity 1.36</p> <p>Freezing point: No Data Found</p> <p>Boiling range: 100 - 370°C</p> <p>Evaporation Rate Slower than ether.</p> <p>Flammability: No Data Found</p>	<p>Partition coefficient (n- No Data Found octanol/water):</p> <p>Decomposition temperature: No Data Found</p> <p>Coating VOC g/L 0.00</p> <p>Odor Mild</p> <p>Odor threshold: No Data Found</p> <p>pH: No Data Found</p> <p>Melting point: No Data Found</p> <p>Solubility: No Data Found</p> <p>Flash point (TCC): 212°F, 100°C</p> <p>Appearance White, Colors and Clear.</p> <p>Viscosity No Data Found</p>
--	--

Section 10 - Stability and Reactivity
--

Conditions to Avoid:

Excessive heat, poor ventilation, excessive aging.

Stability:

STABLE

Materials to Avoid:

None known.

No Data Found

Hazardous Decomposition Products:

Thermal decomposition or combustion can produce fumes of carbon monoxide and carbon dioxide.

No Data Found

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Component Toxicity

Routes of Entry:

No Data Found

Exposure to this material may affect the following organs:

Eyes Skin Cardiovascular System Respiratory System

Effects of Overexposure

Acute and chronic effects from short and long term exposure:

Inhalation: Vapor or mist can cause nausea, headache, and irritation of the nose, throat, and lungs .

Eye contact: Direct contact can cause irritation.

Skin contact: Irritating to the skin on repeated or prolonged contact.

Ingestion: If swallowed, can cause irritation, nausea or vomiting.

Section 12 - Ecological Information

Ecological information: No data found.

Component Ecotoxicity

Talc 96 Hr LC50 Brachydanio rerio: >100 g/L [semi-static]

Section 13 - Disposal Considerations

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state, and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

Section 14 - Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Not regulated, Non Hazardous			
IATA	Not regulated, Non Hazardous			
IMDG	Not regulated, Non Hazardous			

Section 15 - Regulatory Information

This SDS has been compiled in accordance with Appendix D of OSHA Hazcom 2012.

United States TSCA Inventory: All components of this product are listed and/or are exempt .

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- 14808-60-7 Quartz Carcinogen
- 13463-67-7 Titanium dioxide Carcinogen

Canada DSL -- Components are listed or exempt:

Quartz 14808-60-7
Titanium dioxide 13463-67-7
Talc 14807-96-6
Limestone 1317-65-3
Water 7732-18-5

SARA 313 Reportable Components:

No Data Found

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

No Data Found

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HEALTH	*	1	HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH
FLAMMABILITY		0	
PHYSICAL HAZARD		0	
PERSONAL PROTECTION			

To the best of our knowledge, the information contained herein is based on data from manufacturers and/or recognized technical sources. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property, or business caused by this material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.

Reviewer Revision

Date Prepared: 15-Mar-23