

LTA-450

Teller Cash Recycler



Outstanding Features

- Up to 12 denominations recycling
- Up to 22,800 notes of storage capacity
- Operation(Transit) cassette is available inside safe for notes loading and unloading
- Optimally configurable cassette options based on various demands in capacity/denomination
- High precision banknote recognition of images, patterns, etc.
- Self-audit and notes loading/unloading without supervisor by operation(transit) cassette



Unique Features

- Up to 600 notes of physical escrow capacity
- Automatic retract of untaken notes
- Automatic deposit of counted notes
- Note transfer module is located outside safe for increased safety and easy maintenance



Powerful Security

- Accurate counterfeit notes recognition
- Note serial number recognition
- Equipped with international standard certified safe



High efficiency

- Smallest footprint
- 8 inch foldable touch screen



SRS Systems Inc.
5885 East Circle Drive STE 130
Cicero, NY 13039
800.875.6565 Toll Free
www.srssystem.com



LTA-450 Technical Information

Specification*			
Main Control Unit	Intel, Memory 4G, SSD 128G, Windows10		
User Interface	8" wide LCD with touch screen		
Cash Recycling Module (CRM)	Denominations	Max. 12 Denomination (by Split CST 6EA)	
	Transaction speed (Deposit / Dispense)	10 ~ 12 notes/sec	
	Cassette capacity**	Recycling CST	Large CST(3,800 notes) up to 6EA, mixed with Split CST
			Split CST(1,500 + 1,500 notes) up to 6EA, mixed with Large CST
		Operation CST	3,800 notes
		Max. Total	22,800 notes
	Deposit hopper max. capacity	500 notes, Continuous feed	
	Withdrawal hopper max. capacity	300 notes/transaction	
	Retract/Reject hopper max. capacity	100 notes	
	Physical Escrow max. capacity	600 notes	
Dimensions	Size (W × H × D)	UL291 : 375 × 1,116 × 793 (mm) CEN-III : 406 × 1,126 × 821 (mm)	
	Weight	UL291 : 480 Kg CEN-III : 540 Kg	
Safe certification	UL291, CEN-III, CEN-IV		
Safety (lock)	Dial Lock (option : electronic or key lock)		
Security alarm (optional)	Shock / Vibration Sensor, Heat Detection Sensor		
Power consumption	Standby	70W	
	Operation	560W	
Noise Level	Standby	46dBA	
	Operation	70dBA	
Power Supply	AC 100-240V		
Environmental conditions	Operation	+5°C to +40°C 25% to 85% relative humidity	

* Specifications are subject to change without prior notice for product improvement.

** Cassette capacity : Based on 0.1mm thickness note

