# Models 906 & 926





## Models 906 & 926

#### SELF-SERVICE COIN BENEFITS

Your choice of full sort or mixed output

#### **Customer-friendly Features**

## Simple Two Button Operation and Easy to Read Prompting Display

#### **Automatic Coin Feed**

Safely feeds coin, providing a more sanitary environment while reducing the chance of user injury

#### **Alloy Count Sensor Technology**

Accurately counts all six U.S. denominations and automatically rejects foreign coins and slugs back to user

#### Quiet


Noise-reducing materials throughout

#### **Optimum Speed**

To meet noise reduction requirements and allow proper time to cross sell products and services



#### **Teller-friendly Features**



#### **Interactive Touch Screen Display**

Enhances balancing, bag removal and reporting functionality — giving tellers instant access for bag status, end-of-day reports and transaction history

#### **Pull-out Shelf**

Easy teller access to the entire counting and sorting mechanism



#### **Simple Receipt Roll Replacement**

#### **Continuous Cleaning Mechanisms**

Remove sand and other small objects during counting process; Automatic debris ejection system removes non-coin debris to trash receptacle

#### **Bag Management Section**

Direct access to all bags through secure doors; coins feed directly into

bags at floor level, minimizing lifting which allows for easy bag removal





#### SPECIFICATIONS

#### **Coins Counted**

U.S. – 1¢, 5¢, 10¢, 25¢, 50¢ and \$1 (SBA) Canada – 1¢, 5¢, 10¢, 25¢, \$1 and \$2

**Counting Speed** Up to 850 coins per minute

Coin Input Automatic feed

#### **Coin Recognition**

5th generation alloy count sensor technology detects coins by 16 different parameters for the highest degree of accuracy

Automatic Debris System Standard

#### **Error Status Messaging**

#### Languages

English; English & Spanish; English & French

#### YOUR CHOICE OF OUTPUT

**Model 906** Full sort with exact bag stops for 6 bags, configurable in single/double bags by denomination, programmable for Federal Reserve half or full bags

**Model 926** Mixed output to 6 bags Programmable by weight or piece count

**Accuracy** 99.995%

Sound Level 56 db

#### **Approximate Dimensions**

 $27\frac{1}{2}$ " W x  $23\frac{1}{4}$ " D x  $44\frac{1}{2}$ " H (68%" H with optional sign)

Note 1: Allow 2" additional depth for power supply on back sided of unit Note 2: Allow up to 1" in potential height above indicated measurements for leveling feet

Net Weight 220 lbs

#### **Power Source**

External 24v power supply with low voltage for reduced power consumption

#### **Operating Temperature Limits**

+41° to 104° F (0° to +40° C)

#### **Options "More Choices"**

- Rear access
- Sign holder
- Deck mounted inspection tray
- Custom colors & wraps
- Digital marketing
- Host communications software

Specifications are approximate and subject to change

### MAGNER

Magner Corporation of America

41 West Street

Middlefield, Connecticut USA 06455

Phone: (800) 243-2624 Fax: (860) 349-1257

Email: solutions@magner.com www.selfservicecoin.com

Form 415-906