



WWW.NKUKU.COM
T:+44(0)1803 866847
E:INFO@NKUKU.COM

ASSEMBLY INSTRUCTIONS

TUBU BRASS SPOT LIGHT

Thank you for purchasing this Tubu Brass Spot Light.
Please read these instructions carefully before commencing any work.
Please keep these instructions for future reference.

WARNING!

It is recommended that this fitting is installed by a qualified electrician. Install in accordance with the IEE wiring regulations and the building regulations. This is a Class I product and must be earthed. To prevent electrocution switch off at mains supply before installing or maintaining this fitting. Ensure no other person can restore the electrical supply without your knowledge. If you are in any doubt please consult a qualified electrician. This light fitting should be connected to a 5 amp fused circuit. If replacing an existing fitting make a note of the connections. Always use the correct type and wattage bulb. Never exceed the wattage stated. When changing bulbs, always switch off the power and allow the old bulb to cool down before handling. Dispose of used bulbs carefully. This product is suitable for indoor use only.

Using a dimmer switch

This product is suitable for use with a dimmer switch.

FIXING INSTRUCTIONS

Make sure you have the following items which are required to install this light fitting: Small electrical screwdriver, cross head screwdriver and insulation tape.

STEP 1

We recommend that the fuse is withdrawn or the circuit breaker is switched off whilst work is in progress. Before removing the existing fitting, carefully note the position of each set of wires. Where a ring/loop circuit exists there will be a fourth set of wires (usually red) that are not connected to the L, N, or E of fitting. This circuit must be kept together in the 4th terminal of connection block, and insulated from the fitting and other wires. The ring/loop will remain live unless isolated at the mains or circuit breaker regardless of the position of the wall switch.

STEP 2

Unscrew the fixing plate from the back of the product. Mark the position of the of the wall screws using the holes in the fixing plate as a template. Drill holes in the marked positions and apply the rawl plugs. Take care to avoid damaging any concealed wiring and pipes. Pass the mains wire through the black conduit and hook up the light using the loop on the white attachment block.

STEP 3

Unscrew the fixing plate from the back of the product. Mark the position of the of the wall screws using the holes in the fixing plate as a template. Drill holes in the marked positions and apply the rawl plugs. Take care to avoid damaging any concealed wiring and pipes. Pass the mains wire through the black conduit and hook up the light using the loop on the white attachment block.

Check that:

- You have correctly identified the house wires.
- The connections are tight.
- No loose strands have been left out of the connection block.
- Cover all exposed areas of the connection block with 2 layers of insulation tape
- Using the screws provided attach wall light by passing the screw through the brass fixing plate and into the rawl plugs fitted in Step 2. Finally, screw the fixing plate back onto the product to screw it to the wall.

STEP 4

Install an E14 bulb not exceeding a maximum wattage of 40W.

STEP 5

Replace fuse or circuit breaker and switch on. Your light is now ready for use.

CARE AND CLEANING

Finish – We recommend cleaning with a soft dry cloth. Do not use abrasive materials as these will damage the finish.

SAFETY INFORMATION

For your safety, switch off the mains supply before changing light bulbs or cleaning.

