**SDS NO: 4027** 



# 1. IDENTIFICATION OF THE PRODUCT AND COMPANY

## **Product Details:**

**Product Name** Fast Dry Pigmented Sealer

Other Names(s) Pig Sealer
Recommended Use Product Code DG Class/es 3
UN No: 1263

## **Supplier Details:**

**Company** APCO COATINGS (NZ) LIMITED

Address 14 Ron Driver Place, East Tamaki, Auckland 2163, New

Telephone 09 273 3041 Fax 09 273 3045

E Mailcontact@apconz.co.nzWebwww.apcocoatings.co.nz

# **Emergency Telephone Numbers:**

**NZ POISON** 0800 POISON (0800 764 766) **CHEMWATCH** 0800 CHEMCALL (0800 243 622)

NZ Emergency Services

111

## 2. HAZARD IDENTIFICATION

# Hazard Clasification of the mixture:

#### **Hazchem Category:**

3.1C,6.1D,6.1E,6.3A,6.3B,6.4A,6.5B,6.6A,6.7A,6.7B,6.8B,6.9A,6.9B, 9.1A,9.1B,9.1C,9.2A,9.3B, 9.3C

# GHS Classification & Legend:

Information extracted from the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) and the HSNO Act equivalent

**Determined By Chemwatch us-Inf:** No Information at hand **GHS/HSNO Criteria:** 

- 3.1C Substance is harmful through combustion
- 6.1D Substance is toxic if exposed through the skin, ingested or inhaled.
- 6.1E Substance is toxic if exposed through the skin, ingested or inhaled.
- 6.3A Skin corrosion/irritation
- 6.3B Skin corrosion/irritation
- 6.4A Substance that is irritating to the eyes.
- 6.5B Skin Sensitisation
- 6.6A This product can cause germ cell mutagenicity
- 6.7A This product is recognised as a Carcinogen
- 6.8B Substance is toxic to reproductive systems

Version No: 3 Date: 20/04/2017 Page 1 of 10

**SDS NO: 4027** 



6.9A Substance is toxic to specific organs through repeated exposure

6.9B Substance is toxic to specific organs through a single exposure

9.1A Substance is acutely toxic to the aquatic environment

9.1B Substance is chronically toxic to the aquatic environment

9.1C Substance is chronicaly toxic to the aquatic environment

9.2A Substance is Ecotoxic to the soil environment

9.3B Substance is Ecotoxic to terrestrial vertebrates

9.3C Substance is toxic to terrestrial vertebrates

#### Visible Identification:

HSNO Label:









#### Danger Keep out of the reach of Childern.

#### **Hazard Statement:**

As of March 2009, the relevant New Zealand regulations under the <u>Hazardous Substances and New Organisms Act 1996</u> do not specify the exact wording required for hazard statements. The following hazards recognised by the GHS apply to this product with the severity dependent on the exposure levels:

# Physical Hazard (s) - N/A

# Health Hazard (s)

H303: Harmful if swallowed.

H304: Maybe fatal if swallowed and enters the airways

H315: Causes skin irritation.

H316: Causes mild skin irritation

H317: May cause an allergic skin reaction

H319: Causes serious eve irritation.

H332: Harmful if inhaled.

H333: May be harmfull if inhaled

H335: May cause respiratory irritation

H340: May cause genetic deffects

H350: May cause cancer

H351: Suspected of causing cancer.

H361: Suspected of damaging fertility or the unborn child

H372: Causes damage to organs through prolonged or repeated exposure

H373: May cause damage to organs through prolonged or repeated exposure

Version No: 3 Date: 20/04/2017 Page 2 of 10

**SDS NO: 4027** 



# **Enviromental Hazard (s)**

H400: very toxic to aquatic life

H411: Toxic to aquatic life with long lasting effects...

# 3. COMPOSITION / INFORMATION OF INGREDIENTS

Components Alkyd Resin	CAS Number	Proportion 12-28%
Medium Aliphatic Solvent Naptha	64742-88-7	10-30%
White Spirits Ethyl Benzene Titanium Dioxide	100-41-4 100-41-4 13463-67-7	12-20% <0.1% 18-25%
Innert fillers	Mixture	15-25%
Driers	Mixture	<3%
Meko Other Additives	96-29-7	<0.5% <2.5%

## 4. FIRST AID MEASURES

#### First Aid Measures:

Eye Contact	Immediately flush	eyes with plent	y of water and remove
-------------	-------------------	-----------------	-----------------------

contacts where possible, ensure that the eyes are flushed for 20 minutes with the eyes wide open. If the person feels unwell or irritation persists then take those exposed to the

doctor.

**Skin Contact** Immediately wash affected area on the skin with soap

and water for 20 minutes and ensure clothing and footwear is removed immediately if possible. Seek medical advice if large areas of skin are involved or

irritation persists.

**Inhalation** Exposure to high vapor concentrations may cause eye

and respiratory tract irritation, headaches,

dizziness, nausea, uncoordination, drowsiness, and loss of consciousness. Immediately remove the person to a fresh air environment away from harm. If their breathing is difficult give them oxygen and or give cardiopulmonary

Resusitation if breathing has stopped. if breathing difficulties persist take them to the doctor immediately.

**Ingestion (Swallowed)** If swallowed, do NOT induce vomiting. Rinse mouth. Get

medical attention. If spontaneous vomiting occurs, hold patients head below hips to avoid possible aspiration of vomitus into lungs. Never give anything by mouth to an unconscious person. seek medical advice immediately

**Advice to Doctors**: Treat according to symptoms. Repeated or prolonged exposure by inhalation to mixed hydrocarbons may result in dizziness, weakness, irritability, lack

Version No: 3 Date: 20/04/2017 Page 3 of 10

**SDS NO: 4027** 



of concentration and memory loss, tremor of extremities, e.g. fingers, weight loss, anemia, ill-effects to liver and kidneys.

Auditory system effects may include temporary hearing loss and/or ringing in the ears. This product is suspected of damaging fertility or the unborn child. In addition it may cause damage to organs through prolonged or repeated exposure.

#### **Emergency overview:**

For advice in an emergency, contact the Poisons Information Centre or **if breathing** difficulties are acute take thos affected to the doctor or A&E immediately.

# 5. FIRE FIGHTING MEASURES

# Hazards from combustion products:

This product is flammable with a flashpoint of 41°C

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides o nitrogen.

## **Extinguishing Media:**

Water fog, water spray, dry chemical, foam, carbon dioxide

#### Precautions in connection with fire:

Fire fighters should wear full protective clothing and self-contained breathing a pparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and water courses.

# 6. ACCIDENTAL RELEASE MEASURES

## **Emergency Procedure:**

Clear area of all unprotected personnel and notify the local authorities where contamination of sewers or waterways has occurred advise emergency services. Wear full protective equipment and respirators where mist or vapors exist in unknown quantities.

- If inhalation risk exists, use local exhaust ventilation.
- · Vapours are heavier than air.
- · Place a barrier between the workers and the hazard.

# Large amounts:

Do not allow the product to enter drains, sewers or waterways. Dike and soak up with inert material such as dry sand, and vermiculite. Remove liquid to containers for recovery and separate inert material to containers away from the recovered liquid. Ensure the clean up of this material in accordance with local authority bylaws.

Version No: 3 Date: 20/04/2017 Page 4 of 10

**SDS NO: 4027** 



#### Disposal and cleaning of equipment:

Dispose of waste generated from the clean up of this material in accordance with local authority bylaws. All cleaning aides and equipment must be cleaned without letting the waste run into waterways, drains and sewers, tools used to clean up must be non sparking.

### Methods and materials for containment and clean up:

Dispose of waste generated from the clean up of this material in accordance with local authority by laws. All cleaning aides and equipment must be non sparking and cleaned in accordance with national, regional and local authority bylaws

## 7. HANDLING AND STORAGE

Avoid contact with eyes and skin. Wear overalls, impervious gloves and safety glasses.

# Precautions for safe handling:

Read product label before use.

This product and vapours are highly flammable.

Do not open near open flame, sources of heat or ignition.

No smoking.

Keep container closed and Handle containers with care.

Open slowly to control possible pressure release.

Material will accumulate static discharge so use grounding leads to avoid discharge (electrical spark) spark-free tools and equipment suitable for flammables.

Do not use plastic buckets.

Use outdoors or in well-ventilated area.

Wear personal protective equipment.

Wash hands with soap and water after handling.

Wash protective clothing separate to household laundry.

#### Conditions for safe storage:

Keep out of reach of children.

This product will fuel a fire ,Do not store near acids and keep away from oxidising agents

Store in cool, dry, well ventilated place and out of direct sunlight

Keep container tightly closed.

Store at room temperature-donot freeze

Keep away from heat and sources of ignition.

Segregate from food and feed sources

Avoid release to the environment

Do Not contaminate drinking water, through storage or disposal.

Version No: 3 Date: 20/04/2017 Page 5 of 10

**SDS NO: 4027** 



# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Health Exposure Standards:**

Note: (N/A Not availabl in WES)

Source Material TWA STEL Peak Notes

New Zealand Workplace Exposure Standards (WES)

**Exposure Controls:** wear the appropriate PPE

Personal Protection











# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** White

Odour Solvent Colour
Solubility in water (g/l) Immicible
Flash Point (°C) 41° C
Boiling Point (°C) 150° C

**Melting point / freezing point (°C)**Not applicable

Vapour Pressure (Pa) at 20degC370Specific Gravity (Kg/Ltr)1.15-1.25% of Volatile (wt)100

pHVOC (g/l)Not applicableNot applicable

# 10. STABILITY AND REACTIVITY

## **Chemical Stability:**

Stable under normal conditions of storage and handling

# **Hazardous Reactions:**

There is a possibility of explosion if subject to heat source or open flame and sparks.

#### Conditions to avoid:

Store away from heat, flame and sparks.

Version No: 3 Date: 20/04/2017 Page 6 of 10

**SDS NO: 4027** 



## 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects:

### Ingestion:

may cause vomiting and aspiration into lungs and cause chemical pneumonitis or pulmonary odema. If swallowed, symptoms may include headaches, nausea, dizziness and tracheal burning.

#### **Eve Contact:**

This product may be irritating to the eyes resulting in tearing and redness but will not permanently damage eye tissue.

#### Skin Contact:

This product can be moderately irritating to the skin. Prolonged or repeated exposure may defat skin leading to drying, cracking and possibly non-allergenic contact dermatitis.

#### Inhalation:

Vapours may cause discomfort or irritation to the upper respiratory tract. Symptoms of over-exposure may be coughing, choking, wheezing, difficulty in breathing, drowsiness and dizziness.

#### **Chronic Effects:**

Repeated or prolonged exposure by inhalation to mixed hydrocarbons may result in dizziness, weakness, irritability, lack of concentration and memory loss, tremor of extremities, e.g. fingers, weight loss, anemia, ill-effects to liver and kidneys. Auditory system effects may include temporary hearing loss and/or ringing in the ears.

#### Toxicity:

This product is suspected of damaging fertility or the unborn child. In addition it may cause damage to organs through prolonged or repeated exposure.

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity:**

Do not discharge product to sewer, drains or waterways.

# Aquatic toxicity:

This product has been classified as being toxic to aquatic life with long-term effects.

# Persistence/degradability:

Not expected to be persistent or bioaccumulative. However contains components that may not be readily biodegradable. Degrades rapidly in air.

#### Mobility:

Product is not miscible with water however is highly mobile in soil and may contaminate groundwater.

Product is highly volatile and will evaporate to air.

Version No: 3 Date: 20/04/2017 Page 7 of 10

**SDS NO: 4027** 



#### Large amounts:

Do not allow the product to enter drains, sewers or waterways. Dike and soak up with inert material such as dry sand, vermiculite. Remove liquid to containers for recovery and separate inert material to containers using non spark equipment and away from the recovered liquid. Ensure the clean up of this material in accordance with local authority bylaws.

#### Disposal and cleaning of equipment:

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national, regional and local authority regulations. Packaging may still contain product vapours. Allow container to dry before disposal. Do not use container for storing other products. **Do Not** let clean up residue enter storm water, sewers or waterways and clean up in accordance with national, regional and local authority regulations.

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods:

Dispose of product through waste management facility for solvent recovery or disposal, e.g. by incineration. Always follow the waste treatment procedures of national, regional and local authority regulations. Ensure that authorised contractors and or approved handlers dispose of the product and its containers.

Version No: 3 Date: 20/04/2017 Page 8 of 10

**SDS NO: 4027** 



# 14. TRANSPORT INFORMATION

# Required visible identification (Labels):







HAZCHEM 3YE

## Land Transport (UN):

UN Number 1263
Packing Group III
UN proper shipping name Paint

**Environmental hazard** contain and follow spill information clause (6)

Transport hazard class(es)

Class 6 and 9 and must comply with the Rail / Land

Transport hazard class(es)

Transport Rule 45001 & NZS 5433

Special precautions N/A

# Air Transport (ICAO-IATA / DGR):

UN Number 1263
Packing Group III
UN proper shipping name Paint

Environmental hazard contain and follow spill information clause (6)

Transport hazard class(es) Class 6 and 9 and must comply with

AirCivil Aviation Rule Part 92, ICAODangerous Goods

NZ and International

Special precautions N/A

## Sea Transport (IMDG-Code / GGV See):

UN Number 1263
Packing Group III
UN proper shipping name Paint

**Environmental hazard** contain and follow spill information clause (6)

Class 6 and 9 and must comply with

Transport hazard class(es) Sea Maritime Rule 24A and IMDG Dangerous Goods

NZ and International

Special precautions N/A

Version No: 3 Date: 20/04/2017 Page 9 of 10

**SDS NO: 4027** 



#### 15. REGULATORY INFORMATION

#### Reference material:

- EPA January 2012 EPA0094, Labelling of hazardous substance.
- EPA January 2012 EPA0125, Correlation between GHS and New Zealand HSNO Hazard Classes and Categories.
- HSNO act 1996 and Dangerous Goods 2005 and all subsequent amendments.
- Workplace Eposure Standards for Airborne containments (ISBN 978-1-74361-055-8) Online pdf
- Health and Safety at Work Act 2015 and the Health and Safety at work Regulations 2016
- · Sea Maritime Rule 24A and IMDG Dangerous Goods NZ and International
- AirCivil Aviation Rule Part 92, ICAODangerous GoodsNZ and International
- Rail Land Transport Rule 45001/1 & NZS 5433

## 16. OTHER INFORMATION

## **Definitions and abbreviations:**

CAS No Chemical Abstract Number

**ERMA** Environmental Risk Management Authority

PC-TWA Permissible Concentration – Time Weighted Avarage PC-STEL Permissible Concentration – Shot Term Exposure Limit

**HSNO** Hazaradous Substance and New Organisms

**WES** Workplace Exposure Standard

**TEEL** Temporary Emergency Exposure Limit

**IDLH** Immediately Dangarous to Life or Health Concentrations

**OSF** Odur Safety Factor

NOAEL No Observed Adverse Effect Level
LOAEL Lowest Observed Adverse Effect Level

TLV Threshold Limit Value
LOD Limit Of Detection
OTV Odur Threshold Value
BCF BioConcentration Factors
BEI Biological Exposure Index
STEL Short Term Exposure Limit

#### Note:

The information in this SDS was obtained from sources, which we believe were reliable at the time of creating this SDS. However, the information is provided without any presentation or warranty, expressed or implied, regarding its accuracy. The information and recommendations herein, are to the best of our knowledge, true and accurate. No Warranty, express or implied is made or intended.

Version No: 3 Date: 20/04/2017 Page 10 of 10