







### 5550 Jurupa St, Ontario, CA 91761 🔘

# 12V 100Ah LiFePO<sub>4</sub> BATTERY

LITHIUM IRON PHOSPHATE BATTERY

# 1. Features and Applications

A full range of replacement lead-acid batteries, products cover 12V6AH-12V300AH.

Widely used in RV, UPS, fire protection and other backup power scenarios.

Consistent with the appearance and size of the existing lead-acid battery, perfect replacement.

#### 2. Main Parameters

Lithium iron phosphate battery, more reliable and safer.

Rated voltage: 12.8V

Voltage range: 11.0V-14.4V

Capacity range: 6Ah to 300Ah

Supports four batteries in series with a voltage of 48V.

Four batteries supported to be connected in parallel to meet large capacity requirements.

## 3. Optional Functions

Bluetooth function, mobile APP to query battery parameters.

Communication function: RS485 communication or CAN communication.

Display function: The LCD screen displays battery data.



# **Specification**

Nominal Voltage	12.8V
Nominal Capacity	100Ah
Battery Energy	1280Wh
Internal Resistance	≤50 mΩ
Cycle Life 500	0 Cycles @0.3C Charging/Dis-
	charging, DoD 80%
Self Discharge	≤3% per month at 25°C
Standard Charging	
Charge Voltage	14.4V
14.4V at a the con:	45°C temperature, charged to a constant current of 0.2C, and en,changed continuously with stant voltage of 14.4V until the rent was not more than 0.02C
Charge Current	30A
Max.Charge Current	50A
Peak.Charge Current	100A
Standard Discharging	
Discharging Cut-off Voltage	10.8V
Discharging Current	50A
Max. Continuous Current	100A
Max.Pulse Current (<3S)	200A
Operating Condition	
Charge Temperature	0°C to 55°C(32°F to 131°F)
Discharge Temperature	-20°C to 60°C(-4°F to 140°F)
Storage Temperature	0°C to 40°C(32°F to 104°F)
Protection Grade	IP65
Structure & Safety	
Cell & Format	3.2V 100Ah & 4S1P
Casing	ABS+PC
Dimension(L*W*H*)	330*175*216mm / 13*6.9*8.5 In
Weight	12kg / 26.5lb
Terminal	М6
Certificat	UN38.3/MSDS